



TOWN OF BURLINGTON
DEPARTMENT OF PUBLIC WORKS

2025 TRAFFIC SIGNAL IMPROVEMENT PROJECT

WINN STREET AT MOUNTAIN ROAD
Contract #25C-411-0044

This is an unofficial Bid Spec. If this document is used to submit a bid then you must email your contact information to Engineering@burlington.org in order to be added to the bidders list.

Department of Public Works
25 Center Street
Burlington MA 01803

March 5, 2025

Table of Contents

INVITATION FOR BID.....	3
PROJECT DESCRIPTION.....	4
INSTRUCTIONS TO BIDDERS	5
FORM OF GENERAL BID	11
ADDENDA	12
BID FORM.....	13
TOTAL BID PRICE.....	14
CONTRACTOR REFERENCES	15
CONTRACTOR CERTIFICATION	16
AGREEMENT	17
SPECIAL CONDITIONS.....	18
SPECIFICATIONS	36
APPENDIX A – <i>Prevailing Wage Rates</i>	82
APPENDIX B – <i>Plans</i>	82

INVITATION FOR BID

PUBLIC WORKS CONSTRUCTION

Sealed bids for *2025 TRAFFIC SIGNAL IMPROVEMENT PROJECT – WINN STREET AT MOUNTAIN ROAD, CONTRACT 25C-411-0044* must be received by Department of Public Works, Town Hall Annex, 25 Center Street, Burlington, Massachusetts, 01803 by **March 5, 2025 at 10:00AM** and will be publicly opened and read aloud at such time.

- Specifications and bid forms are available on the Town's website site at: www.burlington.org, under Projects Out to Bid.
- Specifications and bid forms may be obtained at the Department of Public Works, Town Hall Annex, 25 Center Street, Burlington, Massachusetts, 01803 after February 19, 2025 between 8:30 AM and 4:00 PM for a fifty (\$50.00) dollar reproduction cost.
- A bid bond of five (5) percent is required.
- Successful bidder must provide 100% Payment and Performance bonds.
- This project is bid according to MGL 30-39M.
- Town's Designated Representative and point of contact for questions is: Meghan Cavalier, mcavalier@burlington.org, 781-270-1642
- Prevailing wage must be paid per MGL 149 SECT. 26-27D
- The Bidder must be pre-qualified by MassDOT.

PROJECT DESCRIPTION

SCOPE OF WORK

The work under this Contract consists of constructing a new traffic signal at the intersection of Winn Street at Mountain Road.

The work also includes unclassified excavation, cement concrete sidewalks, cement concrete pedestrian curb ramps, granite curb, conduit, pull boxes, signs, pavement markings, new traffic signal system and other incidental work.

All work under this contract shall be done in conformance with the *Standard Specifications for Highways and Bridges* dated 2024; the *2017 Construction Standard Details*, the *1990 Standard Drawings for Signs and Supports*; *The 2015 Overhead Signal Structure and Foundation Standard Drawings*, the *2009 Manual on Uniform Traffic Control Devices (MUTCD)* with *Massachusetts Amendments* and the *Standard Municipal Traffic Code*; the *1968 Standard Drawings for Traffic Signals and Highway Lighting*; the latest edition of *American Standard for Nursery Stock*; the Town of Burlington Standards, the Plans and these Special Provisions.

The General Conditions, Supplementary Conditions and Special Provisions shall take precedence over the General Requirements of Division I of the Standard Specifications.

THE PAYMENT CLAUSES CONTAINED IN THE MASSACHUSETTS HIGHWAY DEPARTMENT STANDARD SPECIFICATIONS DO NOT APPLY TO THIS CONTRACT.

THIS WORK SHALL BE BID ON A LUMP SUM BASIS. THE CONTRACT LUMP SUM PRICE SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT AND INCIDENTAL COSTS REQUIRED TO COMPLETE THIS WORK, EXCEPT FOR POLICE SERVICES, WHICH WILL BE PAID FOR ON A REIMBURSABLE BASIS.

INSTRUCTIONS TO BIDDERS

Receipt and Opening of Bids

The Town of Burlington, Massachusetts, herein called the Owner, acting by and through its Department of Public Works, will receive sealed bids as specified in the invitation for Bids at which time bids will be publicly opened and read.

Any bid may be withdrawn prior to the above scheduled time for the opening of bids or authorized postponement thereof. Any bid received after the time and date specified will not be considered. The bidder agrees that this bid will be good and may not be withdrawn for a period of thirty (30) days, Saturdays, Sundays, and legal holidays excluded, after opening the bids.

Location and Work to be Done

The Location of the Work to be done is described in the project description.

The Contractor will furnish all labor, services, materials, equipment, plant, machinery, apparatus, appliances, tools, supplies, and all other things necessary to do all work required for the completion of each item of the Work and as herein specified.

The Work to be done and paid for under any item will not be limited to the exact extent mentioned or described but will include all incidental work necessary or customarily done for the completion of that item.

Preparation of Bid

Each bid must be submitted on the prescribed form. All blank spaces for bid prices must be filled in, in ink or typewritten, in both words and figures.

Each bid must be submitted in a sealed envelope bearing on the outside **the name of the bidder, his address, and endorsed with the name of the project as specified in Receipt and Opening of Bids.**

If forwarded by mail, the sealed envelope containing the bid must be enclosed in another envelope addressed as specified in Receipt and Opening of Bids.

The following sections need to be filled out and completed as part of the bid package;

- Form of General Bid
- Acknowledgement of Addenda, if any
- Bid Form
- Total Bid Price
- Contractor Reference
- Contractor Certification

Bid Opening Procedure

The following list of requirements will apply to each filed bid. Bids not meeting all the requirements for timeliness and security will be rejected without opening; bids not meeting signature and addenda requirements will be rejected prior to checking of bid amounts.

Bids will be filed at the place and before the time specified in Receipt and Opening of Bids.

Properly executed bid security will be placed in a sealed envelope and will be attached to the outside of the envelope containing the bid.

Bid signatures will be checked.

The total dollar amount of each bid will be read, and the three apparent lowest bids will be selected for further consideration. These three apparent low bids will be read aloud for the benefit of the other bidders and the bid opening procedure will be closed. All those present at the bid opening may arrange a time to examine all bids after the bid opening and after the reading of the three apparent low bids.

Ability and Experience of Bidder

No award will be made to any bidder who cannot satisfy the Owner that he has sufficient ability and experience in this class of work and sufficient capital and resources to enable him to complete the work successfully within the time named. The Owner's decision or judgment on these matters will be final, conclusive, and binding. This Contract will be awarded only to a Contractor who is presently and primarily engaged in the business of maintaining, servicing, or installing traffic control signals and devices.

BIDDER MUST HAVE A MINIMUM OF FIVE (5) YEARS' EXPERIENCE AND HAVE COMPLETED SATISFACTORILY FIVE (5) JOBS WITHIN THAT TIME OF SIMILAR SIZE AND SCOPE.

Bidder must have at least two (2) full time Massachusetts Licensed Electricians employed. Within 10 days after opening of bids, the low bidder must submit a list of the Journeyman Electricians (Massachusetts License) who will perform the electrical work in this contract. Also, the low bidder must submit copies of each Journeyman Electrician's current Massachusetts License.

Bidder must have at least two (2) full time employees that have a minimum of ten (10) years of experience maintaining or installing traffic signal field equipment.

Bidder must have at least two (2) full time employees that are IMSA Signal Technicians Level II.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

All Subcontractors must have a minimum of five (5) years' experience and have completed satisfactorily five (5) jobs within that time of similar size and scope.

The Contractor must submit with his bid proposal a list of five (5) jobs which he has successfully completed, giving the name and the address of these projects so they can be investigated prior to the award of the contract.

The Owner may make such investigations as he deems necessary, and the bidder must furnish to the Owner, under oath if so required, all such information and data for this purpose as the Owner may request.

Condition of Work

Each bidder must familiarize himself fully with the conditions relating to the construction of the project and the employment of labor thereon. Failure to do so will not relieve a successful bidder of his obligation to furnish all material and labor necessary to carry out the provisions of this Contract. Insofar as possible the Contractor, in carrying out his work, must employ such methods or means as will not cause any interruption of or interference with the work of any other Contractor.

Addenda and Interpretations

No interpretation of the bid documents will be made orally. Every request for such interpretation should be in writing addressed to the Town's Designated Representative listed in INVITATION TO BID and to be given consideration must be received at least seven (7) days prior to the date fixed for the opening of bids. Any and all such interpretations and any supplemental instructions will be in the form of written addenda to the Contract Documents. Failure of any bidder to receive any such addendum or interpretation will not relieve such bidder from any obligation under this bid as submitted. All addenda so issued will become part of the Contract Documents.

Laws and Regulations

The bidder's attention is directed to the fact that all applicable State laws, municipal ordinances, and the rules and regulation of all authorities having jurisdiction over construction of the project will apply to the Contract throughout, and they will be deemed to be included in the Contract the same as though herein written out in full.

Bid Security

Each bid must be accompanied by a BID BOND, CASH, or, CERTIFIED CHECK, payable to the Town, in the amount stated in INVITATION FOR BID. Such checks will be returned to all except the three (3) lowest responsible and eligible bidders within five (5) days, Saturday, Sundays, and legal holidays excluded, after the opening of bids, and the remaining checks will be returned promptly after the Owner and the accepted bidder have executed the Contract, or if no notice of intent

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

to award has been presented to the selected contractor within thirty (30) days, Saturdays, Sundays and holidays excluded, after the date of the opening of bids, upon demand of the bidder at any time thereafter.

The said amount is fixed and agreed upon by and between the Contractor and the Owner because of the impracticability and extreme difficulty of fixing and ascertaining the actual damages the Owner would in such event sustain, and said amount is agreed to be the amount of damages which the Owner would sustain and said amount will be retained from time to time by the Owner from current periodical estimates.

Right to Reject Bid

The Owner reserves the right to waive any informality or reject any and all bids and alternate bids, should the Owner deem it to be in the public interest to do so.

The Owner also reserves the right to reject the bid of any bidder that the Owner considers to be unqualified based on the criteria set forth herein.

Time for Completion

The bidder must agree to commence work and to fully complete the project within the time limit stated in SPECIAL CONDITIONS.

Comparison of Bids

In the event that there is a discrepancy in FORM OF GENERAL BID between the lump sum or unit prices written in words and figures, the prices written in words will govern.

Rule for Award of Contract

The Contract will be awarded to “the lowest responsible and eligible bidder” for the Total Price Bid pursuant to General Laws Chapter 30, Section 39M, as amended. Such a bidder will possess the skill ability and integrity necessary for the faithful performance of the work, will be able to furnish labor that can work in harmony with all other elements of labor employed, or to be employed, in the work, and will otherwise comply with all applicable provisions of law. Bidder will execute formal agreement within ten (10) days of the Notice of Award.

Statutes Regulating Competitive Bidding

Any bid that does not comply with the provisions of Massachusetts General Laws Chapter 30, Section 39M as amended, need not be accepted and the Owner may reject every such bid.

Wage Rates

Prevailing Wage Rates as determined by the Commissioner of Department of Labor and Industries under the provision of the Massachusetts General Laws, Chapter 149, Section 26 to 27G, as amended, apply to this project. It is the responsibility

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

of the contractor, before bid opening to request if necessary, any additional information on Prevailing Wage Rates for those trades people who may be employed for the proposed work under this contract.

State schedules of Prevailing Wage Rates are included in the contract documents.

Specifications

All work under this contract shall be done in conformance with the *Standard Specifications for Highways and Bridges* dated 2021; the *2017 Construction Standard Details*, the *1990 Standard Drawings for Signs and Supports*; the *1996 Construction and Traffic Standard Details* (as relates to the Pavement Markings details only); *The 2015 Overhead Signal Structure and Foundation Standard Drawings*, the *2009 Manual on Uniform Traffic Control Devices (MUTCD)* with *Massachusetts Amendments* and the *Standard Municipal Traffic Code*; the *1968 Standard Drawings for Traffic Signals and Highway Lighting*; the latest edition of *American Standard for Nursery Stock*; the Town of Burlington Standards, the Plans and these Special Provisions.

The General Conditions, Supplementary Conditions and Special Provisions shall take precedence over the General Requirements of Division I of the Standard Specifications.

THE PAYMENT CLAUSES CONTAINED IN THE MASSACHUSETTS HIGHWAY DEPARTMENT STANDARD SPECIFICATIONS DO NOT APPLY TO THIS CONTRACT.

THIS WORK SHALL BE BID ON A LUMP SUM BASIS. THE CONTRACT LUMP SUM PRICE SHALL INCLUDE ALL LABOR, MATERIALS, EQUIPMENT AND INCIDENTAL COSTS REQUIRED TO COMPLETE THIS WORK.

Bid Items Not Guaranteed

The successful bidder is not guaranteed all items or the total bid price under this contract. Bidders must understand that like items may be bid under other contracts specifically packaged as one complete project. The successful bidder has no right to similar items bid under other projects. The Owner will specify where and when this contract will be applied to undertake a particular improvement.

Liquid Asphalt Adjustment

Per MGL 30-38A paving or Hot Mix Asphalt items bid under this contract (if any) as subject to liquid asphalt price adjustment.

Tie Bids

In the event of tied bids, wherein two or more responsive and responsible vendors provide the same bid price a coin toss will be used to break the tie.

Unforeseen Office Closure

If, at the time of the scheduled bid opening, Town Offices are closed due to uncontrolled events, the bid opening will be postponed until the next normal business day at the original time specified in the documents. Bids will be accepted until that date and time.

FORM OF GENERAL BID

Bid of _____ (hereinafter called "Bidder")*

(____) a corporation, organized and existing under the laws of the state of _____.

(____) a partnership

(____) a joint venture

(____) an individual doing business as _____

To the Town of Burlington, Massachusetts (hereinafter called "Owner").

Bidder:

The bidder, in compliance with your invitation for bid, examined the Contract Documents and being familiar with all of the conditions surrounding the construction of the proposed project including the availability of materials and labor, hereby propose to furnish all labor, materials, and supplies, and to construct the project in accordance with the Contract Documents within the time set forth in the agreement, and at the prices stated below. These prices are to cover all expenses incurred in performing the work required under the Contract Documents, or which this proposal is a part.

*Insert corporation, partnership or individual as applicable.

ADDENDA

Bidder acknowledges receipt of the following addenda:

No. _____ Dated: _____

BID FORM

ITEMS	QT.	TOTAL
ITEM 1. Traffic Signal Construction	1 LS	\$ _____

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

TOTAL BID PRICE

Total Price Bid: \$ _____

Bid Price in Words: _____

Name: _____

Signature: _____

Title: _____

Company: _____

Address: _____

Phone: _____

**This is an unofficial Bid Spec. If this document is used to submit a bid
then you must email your contact information to
Engineering@burlington.org in order to be added to the bidders list.**

CONTRACTOR REFERENCES

The undersigned offers the following information as evidence of their qualifications to perform the work as bid upon according to all the requirements of the plans and specifications.

1. Have been in business under present name for ____ years.
2. The names and addresses of all persons interested in the bid (if made by a partnership or corporation) as Principals are as follows:

(Attach supplementary list if necessary)

3. The bidder is requested to state below what work of a similar character to that included in the proposed contract they have done, and give references that will enable the Owner to judge their experience, skill and business standing (add supplementary page if necessary).

#	Completion Date	Project Name	Contract Amount	Reference Name	Telephone No.
1					
2					
3					
4					
5					

4. Bank reference _____

(Name)

(Bank)

(Address)

(Telephone No.)

CONTRACTOR CERTIFICATION

NON-COLLUSION

I certify under penalties of perjury that this bid or proposal has been made and submitted under good faith and without collusion or fraud with any other person. As used in this certification, the word “person” means any natural person, business, partnership, corporation, union, committee, club, or other organization, entity, or group of individuals.

TAX COMPLIANCE

Pursuant to Massachusetts General Law Chapter 62C, Section 49A, I certify under the penalties of perjury that, to the best of my knowledge and belief, I am in compliance with all laws of the Commonwealth relating to taxes, reporting of employees and contractors, and withholding and remitting child support.

LABOR HARMONY / OSHA 10-HOUR

I will furnish labor that can work in harmony with all other elements of labor employed or to be employed in the work, and All employees to be employed in the work subject to this bid have successfully completed a course in construction safety and health approved by the United States Occupational Safety and Health administration that is at least 10 hours in duration.

Signature: _____
(Person Signing Bid)

(Name of Business)

AGREEMENT

THIS AGREEMENT, by and between the party of the first part, the Town of Burlington, hereinafter called "OWNER", acting herein through its Town Administrator, and the party of the second part hereinafter called "CONTRACTOR".

WITNESSETH: That for and in consideration of the payments and agreements hereinafter mentioned, to be made and performed by the OWNER, the CONTRACTOR hereby agrees with the OWNER to commence and complete the project described by these bid documents hereinafter called the project, for the sum of the contract price and all extra work in connection therewith, under the terms as stated in the Contract Documents; and at their (its and their) own proper cost and expense to furnish all the materials, supplies, machinery equipment, tools, superintendence, labor, insurance, and other accessories and services necessary to complete the said project in accordance with the conditions and prices stated in FORM OF GENERAL BID, GENERAL CONDITIONS, Contract Documents as prepared by the Owner.

IN WITNESS WHEREOF, the parties to these presents have executed this contract.

\$

Contract Price

AGREED:

Town of Burlington

Owner

Date

Contractor

Contractor

Date

Company Name: _____

Address: _____

In accordance with M.G.L. C. 44, Section 31C, this is to certify than an appropriation in the amount of this contract is available therefore and that the Town Administrator has been authorized to execute the contract and approve all requisitions and change orders.

Account #

Town Accountant

Date

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

SPECIAL CONDITIONS

1. All work under this contract must comply with the most recent edition of the Town of Burlington Department of Public Works; Street Opening/Utility Connection Rules & Regulations.
2. The Contractor must submit, prior to the start of any work, the appropriate current job mix formulas approved by MassDOT Highway Division. The Performance Grade Asphalt Binder (PGAB) must not include any Re-refined Engine Oil Bottoms (REOB).
3. Prior to the commencement of any work the Contractor must obtain a Street Opening permit from the DPW/Engineering Division.
4. The cost of police details will be paid for by the Town of Burlington. The Contractor will be responsible for coordinating and scheduling all police details. If the details are not properly canceled by the Contractor in time, the Contractor will be back-charged all detail costs related to the improper cancellation.
5. The Contractor shall submit a submittals schedule for all materials and equipment required for this Project. Submittals schedule shall indicate required dates for submitting shop drawings, samples, and product data for materials to meet project schedule.
6. The Contractor must submit a Schedule of Values in order to request and receive progress payments under the lump sum bid item. In addition, each request for a progress payment must include the list of Schedule of Values stating which items have been complete and the associated quantities of each item.
7. All certified payroll slips must be submitted as part of the pay requisition package for each individual pay requisition request, for each contractor and sub-contractor that has performed work under this contract, up to date of the current pay requisition before the pay requisition will be processed and paid.
8. Tack coats will be made on all HMA and cement concrete surfaces and joints immediately before new HMA pavement is placed at the application rates set forth in the *Standard Specifications for Highway & Bridges*. Tack coating will be considered incidental to the cost of this item.
9. In addition to the contract warranty, the Contractor warranties concrete sidewalk panels and wheel chair ramps against spalling for a three (3) year period from the date of project substantial completion. Any spalling concrete identified within a three (3) year period will be deemed defective and considered warranty work. Once the defective panels are replaced, the warranty will reset and continue another three (3) year warranty period on all concrete work covered by the original contract.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

10. After installation of new gate boxes and structures, or adjustment of existing gate boxes and structures, all construction debris will be removed providing easy access if need arises. All work and labor needed to furnish and remove the construction debris out of the gate boxes and structures will be considered incidental to the bid price.
11. The payment clauses contained in the *Massachusetts Highway Department Standard Specifications* do not apply to this Contract.
12. This work is bid on a lump sum basis. The Contract lump sum price will include all labor, materials, equipment and incidental costs required to complete this work, except for police services. The cost of police detail officer(s) will be paid for by the Town of Burlington.
13. The Town may direct items labeled to be “removed & stacked” to be “removed & disposed” at no additional cost to the contract price.
14. All excavations in existing asphalt and cement concrete surfaces must be saw-cut.
15. Any clearing, grubbing, hedge trimming will be done in a neat manner to minimize disturbance.
16. Under this contract the Contractor agrees to complete “Punch List of Items” assembled by the Designated Representative. The “Punch List of Items” must be completed before the final payment requisition is processed. All the items will be paid for under the appropriate bid item under this contract.
17. The Contractor will be furnished information and ties for the survey baseline and benchmarks. The Contractor shall perform all survey required for the work.
18. The following traffic management conditions apply and are considered incidental to the contract price:
 - Two (2) way traffic must be maintained at all times
 - Complete compliance with the Traffic Management Plan standards set forth in the *Town of Burlington Department of Public Works Street Opening/Utility Connections Rules & Regulations*, Section 850 of the Standard Specifications, and the Manual on Uniform Traffic Control Devices.
 - Detours not included as part of the Traffic Management Plan will be allowed only upon written authorization from the Owner and the Contractor is responsible for supplying all necessary sign(s) and traffic barrels to which to attach the signs, for the detour.

- Work that will disrupt travel on the existing roadways (lane closures, lane shifts, trenching, etc.) will only be allowed between the hours of **9:00AM and 3:00PM** unless prior approval by the Owner is given.
- The Contractor must provide necessary access for fire apparatus and other emergency vehicles through the work zones at all times.
- The Contractor must provide safe and ready means of ingress and egress to all stores and shops, public and private professional offices and any other businesses or residences in the project area, both day and night, for the duration of the project.
- All sidewalks shall be safe and open to pedestrians by the end of each work shift of the approved work hours. Temporary wheelchair ramps may be needed to maintain access at driveways and intersections.
- The Contractor is responsible for keeping the worksite and travel ways clean of debris. The cost for maintenance and cleaning of travel ways will be considered incidental to the contract price.

19. No work will be allowed on Saturdays, Sundays, or holidays without prior approval by the Owner.

20. Attention is directed to the following parts of the contract:

Description	Location in Contract
Preparation of Bid	Instructions Bidders
Experience of Bidders	Instructions to Bidders
Bid Security	Instructions to Bidders
Execution, Correlation and Intent	General Conditions; Article 1
Contract Administration	General Conditions; Article 2
Superintendent	General Conditions; Article 4, Section 8
Project/Progress Schedule	General Conditions; Article 4, Section 9
Liquidated Damages	General Conditions; Article 6
Prevailing Wage Rates	Appendix A
Project Plans	Appendix B

21. Summary Table of Important Contract Dates

Item	Date
Bid Opening	3/5/25
Commencement of Work No Later Than	5/1/25
Completion of Work No Later Than	10/15/25
Liquidated Damages Starting	10/16/25

GENERAL CONDITIONS

ARTICLE 1

CONTRACT DOCUMENTS

1.1 DEFINITIONS

1.1.1 THE CONTRACT DOCUMENTS

The Contract Documents consist of the Owner-Contractor Agreement, the Conditions of the Contract (General, and other Conditions), the Drawings, the Specifications, all Addenda issued prior to and all Change Orders issued after execution of the Contract, and all applicable laws, ordinances and regulations. The Contract Documents include Bidding Documents such as the Advertisement or Invitation for Bid, the Instructions to Bidders, sample forms, the Contractor's Bid or portions of Addenda relating to any of these, or any other documents, specifically enumerated in the Owner-Contractor Agreement.

1.1.2 THE CONTRACT

The Contract Documents form the Contract for Construction. This Contract represents the entire and integrated agreement between the parties hereto and supersedes all prior negotiations, representations, or agreements, either written or oral. The Contract may be amended or modified only by a written Change Order.

1.1.3 THE WORK

The Work comprises the completed construction required by the Contract Documents and includes all labor necessary to produce such construction, and all materials and equipment incorporated in such construction.

1.1.4 THE PROJECT

The project is the total construction of which the Work performed under the Contract Documents may be the whole or a part.

1.1.5 OR EQUAL

The use of the words "Or Equal" following the name of any manufacturer, vendor or proprietary product will be understood to mean that articles or materials may be substituted which, in the opinion of the Owner, are equal in quality, durability, appearance, strength, design and performance to the articles or materials named or described and will perform adequately in providing a first-class facility.

When submitting shop drawing information on articles or materials which are being proposed as substitutes for specified items, the Contractor must clearly identify them as such. If the articles or materials are accepted as equal to those on which dimensions on the drawings are based, any dimensional variance from those shown and/or specified must be shown on the shop drawings prepared by the Contractor, illustrating the manner in which conformity to dimensions and design is to be obtained. All such drawings will be subject

to the approval of the Owner and the installation of the article will not proceed without first obtaining said approval.

1.2 EXECUTION, CORRELATION AND INTENT

1.2.1

By executing the Contract, the Contractor represents that he has visited the site, familiarized himself with the local conditions under which the Work is to be performed, and correlated his observations with the requirements of the Contract Documents.

1.2.2

The intent of the Contract Documents is to include all items necessary for the proper execution and completion of the Work. The Contract Documents are complementary, and what is required by any one will be as binding as if required by all. Work not covered in the Contract Documents will not be required unless it is consistent therewith and is reasonably inferable there from as being necessary to produce the intended results. Words and abbreviations which have well-known technical or trade meanings are used in the Contract Documents in accordance with such recognized meanings.

1.2.3

The Notice to Proceed will come in the form of a written letter to the Contractor. Once the written Notice to Proceed has been received by the Contractor, that date will be the legal start date for work under the Contract.

In the event of a failure to issue a Notice to Proceed written document specifying the commencement date, the pre-construction meeting date will serve as the Notice to Proceed date.

1.3 OWNERSHIP AND USE OF DOCUMENTS

1.3.1

All Drawings, Specifications and copies thereof furnished by the Owner are and will remain the Owner's property. They are to be used only with respect to this Project and are not to be used on any other project without prior written consent of the Owner. With the exception of one contract set for each party to the Contract, such documents are to be returned or suitably accounted for to the Owner at the completion of the Work. Submission or distribution to meet official regulatory requirements or for other purposes in connection with the Project is not to be construed as publication in derogation of any reserved rights.

ARTICLE 2

ADMINISTRATION

2.1 ADMINISTRATION OF THE CONTRACT

2.1.1

The Owner or its Designated Representative will visit the site at intervals appropriate to the stage of construction to familiarize himself generally with the progress and quality of the Work and to determine in general if the Work is proceeding in accordance with the Contract Documents. However, the Owner's Designated Representative will not be required to make exhaustive or continuous on-site inspections to check the quality or quantity of the Work.

2.1.2

The Owner will at all times have access to the Work whenever it is in preparation and progress. The Contractor must provide facilities for such access so the Owner may perform its functions under the Contract Documents.

2.1.3

The Owner will make payments for completed work, as approved by the Owner, in accordance with M.G.L. Ch. 30, Sec. 39G. A five percent retainage will be deducted from periodic payments to the Contractor.

2.1.4

The Owner will render information necessary for the proper execution or progress of the Work within twenty (20) days of any request by the contractor or in accordance with any time limit agreed upon.

2.1.5

The Owner will have authority to reject Work which does not conform to the Contract Documents. Whenever, in his opinion, he considers it necessary or advisable for the implementation of the intent of the Contract Documents, he will have authority to require special inspection or testing of the Work whether or not such Work is then fabricated, installed or completed. Any such rejection of work will not relieve the Contractor of the responsibility for maintaining protection of the Work and the Owner's property.

2.1.6

The Owner or its Designated Representative will review and approve or take other appropriate action upon Contractor's submittals such as Shop Drawings, Product Data and Samples, but only for conformance with the design concept of the Work and with the information given in the Contract Documents. Such action will be taken with reasonable promptness so as to cause no delay. The Owner's approval of a specific item will not indicate approval of an assembly of which the item is a component.

2.1.7

The Owner will conduct inspections to determine the date of Substantial Completion and Final Completion, will review written warranties and related documents required by the Contract and assembled by the Contractor, and will issue a final Certificate for Payment.

ARTICLE 3

OWNER

3.1 DEFINITION

3.1.1

The Owner is the person or entity identified as such in the Owner-Contractor Agreement and is referred to throughout the Contract Documents as if singular in number and masculine in gender. The term Owner means the Town of Burlington or its designated representative.

3.2 INFORMATION AND SERVICES REQUIRED OF THE OWNER

3.2.1

The Owner will, at the time of execution of the Agreement and any subsequent Change Orders, certify for the Contractor that financial arrangements have been made to fulfill the Owner's obligations under the Contract.

3.2.2

The Owner will furnish all documents describing the work.

3.2.3

Except as provided in Subparagraph 4.7.1. Owner will secure and pay for necessary approvals, easements, assessments and charges required for the construction, use or occupancy of permanent structures or for permanent changes in existing facilities.

3.2.4

Information or services under the Owner's control will be furnished by the Owner with reasonable promptness to avoid delay in the orderly progress of the Work.

3.2.5

The Owner will furnish the Contractor with three (3) copies of all Drawings and Specifications and revisions issued during the progress of the Work; all additional copies will be furnished upon request at the cost of reproduction.

3.2.6

The Owner, through its Designated Represented, will forward all instructions directly to the Contractor.

3.3 OWNER'S RIGHT TO STOP THE WORK

3.3.1

If the Contractor fails to correct defective Work as required by the Owner or fails to carry out the Work in accordance with the Contract Documents or if the Owner will for any other

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

reason so require, the Owner, by a written order signed personally or by an agent specifically so empowered by the Owner in writing, may order the Contractor to stop the Work, or any portion thereof, until the cause for such order has been eliminated or until further written notice from the Owner; however, this right of the Owner to stop the Work will not give rise to any duty on the part of the Owner to exercise this right for the benefit of the Contractor or any other person or entity. The Contractor must resume the Work after such stoppage promptly upon written notice to do so from the Owner. If such stoppage is required through no fault of the Contractor, the Contract Time (and the dates for achieving Substantial Completion and Final Completion) will be extended by a period equal to the period of the stoppage, and the Contractor will be compensated for its reasonable and justifiable cost incurred as a result of such stoppage.

3.4 OWNER'S RIGHT TO CARRY OUT THE WORK

3.4.1

If the Contractor defaults or neglects to carry out the Work in accordance with the Contract Documents and fails within seven days after receipt of written notice from the Owner to commence and continue correction of such default or neglect with diligence and promptness, the Owner may, without prejudice to any other remedy he may have, perform such work or cause such work to be performed and/or make good such deficiencies. In such case an appropriate Change Order will be issued deducting from the payments then or thereafter due the Contractor the cost of correcting such deficiencies, including compensation for additional services made necessary by such default, neglect or failure. If the payments then or thereafter due the Contractor are not sufficient to cover the amount, the Contractor must pay the difference to the Owner.

3.5 OWNER'S RIGHT TO TERMINATE CONTRACT

3.5.1

The Town reserves the right to terminate this Contract at their discretion with thirty (30) days written notice to the contractor. In the event of Contract termination, all finished or unfinished work, or un-used material, already paid for under Contract prices, will become the property of the Town of Burlington.

ARTICLE 4

CONTRACTOR

4.1 DEFINITION

4.1.1

The Contractor is the person or entity identified as such in the Owner-Contractor Agreement and is referred to throughout the Contract Documents as if singular in number and masculine in gender. The term Contractor means the Contractor or his authorized representative.

4.2 REVIEW OF CONTRACT DOCUMENTS

4.2.1

The Contractor must carefully study and compare the Contract Documents and must at once report to the Owner any error, inconsistency or omission he may discover. The Contractor will not be liable to the Owner for any damage resulting from errors, inconsistencies or omissions in the Contract Documents which he discovers but will be liable for damage to the extent he reasonably should have but failed to discover such errors, inconsistencies or omissions. The Contractor will perform no portion of the Work at any time without Contract Documents or, where required, approved Shop Drawings, Product Data or Samples for such portion of the Work.

4.3 SUPERVISION AND CONSTRUCTION PROCEDURES

4.3.1

The Contractor must supervise and direct the Work, using his best skill and attention which will not be less than such state of skill and attention generally rendered by the contracting profession for projects similar to the Project in scope, difficulty and location. The Contractor must maintain adequate supervisory personnel at the Site during the performance of the Work. He will be solely responsible for all construction means, methods, techniques, sequences and procedures and for coordinating all portions of the Work under the Contract.

4.3.2

The Contractor will be responsible to the Owner for the acts and omissions of his employees, Subcontractors and their agents and employees, and other persons performing any of the Work under a contract with the Contractor. This obligation will also extend to the presence on the Site of suppliers of materials or equipment, their employees, contractors, and agents engaged in the work.

4.3.3

The Contractor will not be relieved from his obligations to perform the Work in accordance with the Contract Documents either by the activities or duties of the Owner in its administration of the Contract.

4.4 LABOR AND MATERIALS

4.4.1

Unless otherwise provided in the Contract Documents, the Contractor will provide and pay for all labor, materials, equipment, tools, construction equipment and machinery, water, heat, utilities, transportation, and other facilities and service necessary for the proper execution and completion of the Work, whether temporary or permanent and whether or not incorporated or to be incorporated in the Work.

4.4.2

The Contractor will at all times enforce strict discipline and good order among his employees and will not employ on the Work any unfit person or anyone not skilled in the task assigned to him including all persons on the Site controlled directly or indirectly by the Contractor.

4.5 WARRANTY

4.5.1

The Contractor warrants to the Owner that all materials and equipment furnished under this Contract will be new and of recent manufacture unless otherwise permitted in writing by the Owner and that all Work will be of good quality, free from faults and defects and in conformance with the Contract Documents. All Work not conforming to these requirements, including substitutions not properly approved and authorized, may be considered defective and, promptly after written notification of non-conformance, will be repaired or replaced by the Contractor with Work conforming to such requirements. If required by the Owner, the Contractor will furnish satisfactory evidence as to the kind and quality of materials and equipment.

4.6 TAXES

4.6.1

The Contractor will pay all applicable sales, consumer, use and other similar taxes for the Work or portion thereof provided by the Contractor which are legally enacted at the time bids are received, whether or not yet effective.

4.7 PERMITS, FEES AND NOTICES

4.7.1

Unless otherwise expressly provided in the SPECIAL CONDITIONS, the Contractor will secure and pay for all permits and fees, licenses and inspections necessary for the proper execution and completion of the Work which are customarily secured after execution of the Contract and which are legally required at the time the bids are received, and the same will at all times be the property of the Owner and will be delivered to the Owner upon completion of the Project.

4.7.2

The Contractor must give all notices and comply with all federal, state and local laws, ordinances, rules, regulations and lawful orders of any public authority bearing on the performance of the Work. The Contractor must provide the Owner with reproductions of all permits, licenses and receipts for any fees paid. The Owner represents that it has disclosed to the Contractor all orders and requirements known to the Owner of any public authority particular to this Contract.

4.7.3

If the Contractor observes that any of the Contract Documents are at variance with applicable laws, statutes, codes and regulations in any respect, he must promptly notify the Owner in writing, and any necessary changes must be accomplished by appropriate Modification.

4.7.4

If the Contractor performs any Work which he knows or should know is contrary to such laws, ordinances, rules and regulations, and without such notice to the Owner, he will assume full responsibility therefore and will bear all costs attributable thereto.

4.8 SUPERINTENDENT

4.8.1

The Contractor must employ a competent superintendent and necessary assistants who will be in attendance at the Project site at all times during the progress of the Work. The superintendent will represent the Contractor and all communications given to the superintendent will be as binding as if given to the Contractor. Important communications will be confirmed in writing. Other communications will be so confirmed on written request in each case.

4.9 PROGRESS SCHEDULE

4.9.1

The Contractor, immediately after being awarded the Contract, must prepare and submit for the Owner's information an estimated progress schedule for the Work. The progress schedule must be related to the entire Project to the extent required by the Contract Documents, and will provide for expeditious and practicable execution of the Work. No work will start without the Project schedule. The Contractor must submit the project schedule five days prior to start the work.

4.10 DOCUMENTS AND SAMPLES AT THE SITE

4.10.1

The Contractor must maintain at the site for the Owner one record copy of all Drawings, Specifications, Addenda, Change Orders and other Modifications, and "As-Built"

Drawings and Specifications in good order and marked currently to record all changes made during construction, and approved Shop Drawings, Product Data and Samples. These will be available to the Owner upon completion of the Work.

4.11 SHOP DRAWINGS, PRODUCT DATA AND SAMPLES

4.11.1

Shop Drawings are drawings, diagrams, schedules and other data specially prepared for the Work by the Contractor or any Subcontractor, manufacturer, supplier or distributor to illustrate some portion of the Work.

4.11.2

Product Data are illustrations, standard schedules, performance charts, instructions, brochures, diagrams and other information furnished by the Contractor to illustrate a material, product or system for some portion of the Work.

4.11.3

Samples are physical examples which illustrate materials, equipment or workmanship and establish standards by which the Work will be judged.

4.11.4

The Contractor must review, approve and submit, with reasonable promptness and in such sequence as to cause no delay in the Work or in the work of the Owner or any separate contractor, all Shop Drawings, Product Data and Samples required by the Contract Documents.

4.11.5

By approving and submitting Shop Drawings, Product Data and Samples, the Contractor represents that he has determined and verified all material, field measurements, and field construction criteria related thereto, or will do so, and that he has checked and coordinated the information contained within such submittals with the requirements of the Work and of the Contract Documents.

4.11.6

The Contractor will not be relieved of responsibility for any deviation from the requirements or the Contract Documents by the Owner's approval of Shop Drawings, Product Data or Samples or the Owners' approval of the same unless the Contractor has specifically informed the Designated Representative in writing of such deviation at the time of submission and the Designated Representative has given written approval to the specific deviation. The Contractor will not be relieved from responsibility from errors or omissions in the Shop Drawings, Product Data or Samples by the Owner's approval thereof.

4.11.7

The Contractor must direct specific attention, in writing or on resubmitted Shop Drawings, Product Data or Samples, to revisions other than those requested by the Owner or its Designated Representative on previous submittals.

Designated Representative

4.11.8

No portion of the Work requiring submission of a Shop Drawing, Product Data or Sample will be commenced until the submittal has been approved by the Owner or Designated Representative. All such portions of the Work will be in accordance with approved submittals.

4.12 USE OF SITE

4.12.1

The Contractor will confine operations at the site to areas permitted by law, ordinances, permits and the Contract Documents and must not unreasonably encumber the site with any materials or equipment.

4.13 CUTTING AND PATCHING OF WORK

4.13.1

The Contractor will be responsible for all cutting, fitting or patching that may be required to complete the Work or to make its several parts fit together properly.

4.13.2

The Contractor must not damage or endanger any portion of the Work or the work of the Owner or any separate contractors by cutting, patching or otherwise altering any work or by excavation. The Contractor must not cut or otherwise alter the work of the Owner or any separate contractor except with the written consent of the Owner and of such separate contractor. The Contractor must not unreasonably withhold from the Owner or any separate contractor his consent to cutting or otherwise altering the Work.

4.14 CLEANING UP

4.14.1

The Contractor at all times will keep the premises free from accumulation of waste materials or rubbish caused by his operations. At the completion of the Work he will remove all his waste materials and rubbish from and about the Project in full compliance with all applicable laws and regulations as well as all his tools, construction equipment, machinery and surplus materials and the Project must be thoroughly cleaned and ready for immediate occupancy by the Owner.

4.14.2

If the Contractor fails to clean up at the completion of the Work, the Owner may do so as provided in Paragraph 3.4 and the cost thereof will be charged to the Contractor.

4.15 COMMUNICATIONS

4.15.1

The Contractor must forward all communications to the Owner's designated representative.

4.16.2

The Contractor will at all times have a designated representative in the field that is authorized to act on behalf and make decisions for the Contractor under this contract agreement.

4.16 ROYALTIES AND PATENTS

4.16.1

The Contractor must pay all royalties and license fees. He must defend all suits or claims for infringement of any patent rights and will save the Owner harmless from loss on account thereof, except that the Owner will be responsible for all such loss when a particular design, process or the product of a particular manufacturer or manufacturers is specified, but if the Contractor believes or has reason to believe that the design, process or product specified is an infringement of a patent, he will be responsible for such loss unless he promptly gives such information to the Owner, and thereafter the Owner insists on the use of the design, process or products specified.

4.17 INDEMNIFICATION

4.17.1

To the fullest extent permitted by law, the Contractor will indemnify and hold harmless the Owner, the Designated Representative, and their agents and employees from and against all claims, damages, losses and expenses, including but not limited to attorney's fees, arising out of or resulting from the performance of the Work, provided that any such claim, damage, loss or expense (1) is attributable to bodily injury, sickness, disease or death, or to injury or destruction of tangible property (other than the Work itself) including the loss of use resulting there from, and (2) is caused in whole or in part by any negligent act or omission of the Contractor, any Subcontractor, anyone directly or indirectly employed by any of them or anyone for whose acts any of them may be liable, regardless of whether or not it is caused in part by a party indemnified there under. Such obligation will not be construed to negate, abridge, or otherwise reduce any other right or of indemnity which would otherwise exist as to any party or person described in this Paragraph 4.17.

4.17.2

In any and all claims against the Owner the Designated Representative or any of their agents or employees by any employee of the Contractor, any Subcontractor anyone directly or indirectly employed by any of them or anyone for whose acts any of them may be liable, the indemnification obligation under this Paragraph 4.17 will not be limited in any way by any limitation on the amount or type of damages, compensation or benefits payable by or for the Contractor or any Subcontractor under workers' or workmen's compensation acts, disability benefit acts or other employee benefit acts.

4.17.3

The obligations of the Contractor under this paragraph 4.17 will not extend to the liability of the Owner, the Designated Representative , their agents or employees, arising out of (1) the

preparation or approval of maps, drawings, opinions, reports, surveys, change orders, designs or specifications, or (2) written directions or instructions given by the Owner, the Designated Representative , their agents or employees, provided they are the sole cause of the injury or damage.

ARTICLE 5
INSURANCE

Contractor must provide insurance as specified below:

General Liability

Includes:

- Comprehensive form
- Premises/Operations
- Underground Explosion & Collapse Hazard
- Products / Completed Operations
- Independent Contractors
- Broad From Property Damage
- Personal Injury

Each Occurrence	\$1,000,000
Aggregate	\$2,000,000

Automobile Liability

Includes:

- All Owned Vehicles
- Hired Vehicles
- Non-owned Vehicles

Bodily Injury & Property Damage Combined	\$1,000,000
--	-------------

Workers Compensation & Employers Liability

- As Required by State of Massachusetts

Each Accident	\$100,000
Bodily Injury by Disease (Policy Limit)	\$500,000
Bodily Injury by Disease (Each Employee)	\$100,000

Additional Insurance / Requirements

- The Town of Burlington Will be named as Additional Insured

ARTICLE 6
LIQUIDATED DAMAGES

6.1 LIQUIDATED DAMAGES

If the Contractor neglects, fails or refuses to complete the work as herein specified, or any proper extension thereof granted by the Owner, then the Contractor does hereby agree, as a part consideration for the awarding of this Contract, to pay to Owner the amount of \$1,000 per day, not as a penalty but as liquidated damages for such breach of Contract as hereinafter set forth, for each and every calendar day that the Contract will be in default after the date stipulated in the Contract for completing the work.

SPECIFICATIONS

PERSONAL PROTECTIVE SAFETY EQUIPMENT FOR CONTRACTOR PERSONNEL

The Contractor is responsible to ensure that all personnel, including all subcontractors, working on the project are issued and are wearing all necessary personal protective safety equipment while working within the project limits. This equipment shall include, as a minimum, a hardhat and a safety vest, regardless of the type of work being performed. Other safety equipment shall be added as required to perform the work in which they are engaged and in accordance with all local, state and federal requirements in effect. Safety equipment shall be provided at no additional cost.

PROTECTION OF UNDERGROUND FACILITIES

The locations of utilities shown on the Plans are approximate and have been plotted from field survey and record plan information. The Contractor's attention is directed to the necessity of making his own investigation in order to assure that no damage to existing structures, drainage lines, water or sewer lines, traffic signal conduits, etcetera, will occur.

The Contractor shall notify Massachusetts DIG SAFE and procure a Dig Safe Number for each location prior to disturbing existing ground in any way. The telephone number of the Dig Safe Call Center is 1-888-344-7233.

WORK SCHEDULE

No work that will disrupt travel on the existing roadways (lane closures, lane shifts, trenching, etc.) shall be done from 6:00AM to 9:00AM and from 3:00PM to 6:00PM.

Work on this project is restricted to a normal eight-hour day, five-day week, with the Contractor and all Subcontractors working on the same shift.

No work shall be done on this Contract on Saturdays, Sundays or holidays or on the day before or the day after a long weekend which involves a holiday without prior approval by the Engineer.

A written request shall be issued by the Contractor for any requested deviation to the work day or times indicated in the permit. Night work may be allowed for select construction activities (utility connections, paving, pavement marking installation, etc.) as approved by the Engineer and the Town of Burlington.

TRAFFIC MANAGEMENT PLAN

Before starting any work under this Contract, the Contractor shall prepare, and submit to the Engineer and Town a plan that indicates the traffic routing proposed by the

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

Contractor during the various stages, time periods of the work, and the temporary traffic control devices to be employed during each stage and time period of the work to maintain traffic and access to abutting properties.

Particular care shall be taken to establish and maintain methods and procedures that will not create unnecessary or unusual hazards to public safety. Traffic control devices required only during working hour operations shall be removed at the end of each working day.

Safety devices and sign placement shall conform to the applicable sketches shown in the standard Temporary Traffic Control Plan (TTCP), conforming to the MUTCD, available at the MassDOT's website: www.massdot.state.ma.us/highway.

Under no circumstance should a Contractor close a travel lane or in any way affect traffic outside the specified work hours without approval from the town. Travel lanes of the roadway must be fully open to traffic prior to the start and after the end of the approved work schedule. In no case will operations commence prior to specified work hours without approval from the Town. This includes traffic set-ups that restrict the flow of traffic.

The Contractor shall notify the Engineer in writing two (2) weeks in advance of any proposed temporary roadway closures necessary to complete the work. Work on roadways shall proceed only on such sections and widths thereof as will be approved by the Engineer.

The Contractor shall serve written notice to all abutters two weeks in advance of any reconstruction work adjacent to their property, and during such time that construction is in progress, provide safe access to the abutting properties. The Contractor shall always schedule his operations to minimize interruption to the normal flow of traffic.

The Contractor shall provide safe and ready means of ingress and egress to all stores and shops, public and private and professional offices, and any other businesses or residences within the project limits, both day and night, for the duration of the project. Any temporary access disruption during business hours shall be coordinated with the owner prior to scheduling the work.

The Contractor shall also prepare and submit a three (3) week schedule of activities and locations to the Engineer and the Town for posting on the Town's Website for public information.

All sidewalks shall be safe and open to pedestrians by the end of each work shift of the approved work hours. Temporary pedestrian curb ramps may be needed to maintain access at driveways and intersections.

The Contractor is responsible for sweeping and cleaning of surfaces beyond the limits of the project required to clean up material caused by spillage or vehicular tracking during the various phases of the work. The Contractor is responsible for repairing roadways damaged by construction vehicles. Payment for maintenance and cleaning of roads will not be paid for separately but shall be considered as incidental to the work being performed under the Contract and there will be no additional compensation.

Signs having messages that are irrelevant to normal traffic conditions shall be removed or properly covered at the end of each work period. Signs shall be kept clean at all times and legends shall be distinctive and unmarred.

SHOP DRAWING SUBMITTALS

(Supplementing Subsection 5.02)

The Contractor shall submit a submittals schedule for all materials and equipment required for this Project. Submittals schedule shall indicate required dates for submitting shop drawings, samples, and product data for materials to meet project schedule.

No changes shall be made to the approved drawings without the written consent of the Engineer.

PLANS

(Supplementing Subsection 5.02)

The Contractor shall furnish Mylar "AS BUILT" plans of the completed project to the Engineer. These "AS BUILT" plans shall be furnished prior to the date of final acceptance.

No separate payment will be made for "AS BUILT" plans, but all costs in connection therewith shall be included in the prices bid for the various Contract items of work.

"AS BUILT" plans shall contain all information shown on the contract drawings and shall clearly indicate areas where changes were made during construction.

The "AS BUILT" plans shall be titled "AS BUILT" and stamped and dated by a Professional Engineer of the appropriate discipline registered in Massachusetts. The Professional Engineer's stamp is required to certify any changes made to the contract drawings and shall not dictate responsibility for the original design drawings.

The "AS BUILT" plans will provide a record of constructed improvements that include signal system layout, utility infrastructure, aerial utilities, and walls. The "AS BUILT" plans are for future reference; therefore partial plan sets will not be accepted. The Contractor may elect to use a combination of reproducible duplicates of the design drawings and revised CAD drawings to provide a complete set of "AS BUILT" plans.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

COOPERATION OF THE CONTRACTOR
(Supplementing Subsections 5.05 and 5.06)

Agents of various public service agencies, municipal and State Departments, and private site contractors may be entering on the work site to remove existing utilities, to construct or place new facilities or to make alterations to existing facilities.

The Contractor shall perform the work in cooperation with the various agencies in a manner which causes the least interference with the operations of the aforementioned agencies and shall have no claim for delay which may be due, or result, from said work of these agents.

CONSTRUCTION STAKING
(Supplementing MassDOT Subsection 5.07)

The Contractor will be furnished information and ties for the survey baseline and benchmarks. The Contractor shall perform all survey required for the work.

PUBLIC SAFETY AND CONVENIENCE
(Supplementing Subsection 7.09)

The Contractor shall provide necessary access for fire apparatus and other emergency vehicles through the work zones to abutting properties at all times.

Sweeping and cleaning of surfaces beyond the limits of the project required to clean up material caused by spillage or vehicular tracking during the various phases of the work shall be considered as incidental to the work being performed under the Contract and there will be no additional compensation.

NOTICE TO OWNERS OF UTILITIES
(Supplementing Subsection 7.13)

Written notice shall be given by the Contractor to all public service corporations or municipal and State officials owning or having charge of publicly or privately owned utilities at least one week in advance of the commencement of operations that will affect the utilities. The Contractor shall, at the same time, file a copy of such notice with the Engineer.

Before commencing work on service connections, the Contractor shall be responsible for contacting the Electric Company servicing the area to obtain construction requirements, standards, and to give adequate notice of commencement of work. The Contractor's attention is further directed to the requirements of Work in the Immediate Vicinity of Certain Underground Structures and Poles herein included in these Special Provisions.

The following are the names of owners and representatives of the principal utilities affected, but completeness of this list is not guaranteed:

TOWN OF BURLINGTON

Burlington Fire Department
29 Center Street
Burlington, MA 01803

Michael Hanafin
Fire Prevention Captain
Phone:(781)-238-5640

Burlington Police Department
45 Center Street
Burlington, MA 01803

Chief Thomas Brown
Phone:(781)-505-4920

Department of Public Works
25 Center Street- Annex Building
Burlington, MA 01803

Meghan Cavalier, P.E.
Assistant Town Engineer
Phone:(781)-270-1640

ELECTRIC

Eversource Electric
247 Station Drive, NWBED 180
Westwood, MA 02090

Steve Owens
Phone:(508)-441-5881

TELEPHONE

Verizon
385 Myles Standish Blvd
Taunton, MA 02780

Karen Mealey
Phone:(774)-409-3160

GAS

National Grid Gas
40 Sylvan Rd
Waltham, MA 02451

Melissa Owens
Phone:(781)-907-2845

Tennessee Gas Pipeline
8 Anngina Drive
Enfield, CT 06082

David Wood
Phone:(860)-763-6005

CABLE

Comcast
676 Island Pond Road
Manchester, NH 03109

Wendy Brown
Phone:(603)-541-1082

RCN

956 Massachusetts Avenue
Arlington, MA 02476

Margot Jones
Phone:(781)-316-8881

AT&T/ TCA, c/o Siena Engineering
50 Mall Road – Suite 203
Burlington, MA 01803

Hayleigh Walker
Phone:(781)-221-8400

OTHER AFFECTED PARTIES ARE:

Vanasse Hangen Brustlin, Inc.
260 Arsenal Place #2
Watertown, MA 02472-4026

David Greenberg, P.E.
Senior Project Manager
Phone :(617)-924-1770

The Contractor shall make his own investigation to assure that no damage to existing structures, drainage lines, traffic signal conduits, and other utilities will occur as a result of construction operations.

The Contractor shall notify "Mass. DIG SAFE" and procure a DIG SAFE number of each location prior to disturbing ground in any way.

"DIG-SAFE" Call Center: Telephone 1-888-344-7233

PROTECTION OF UTILITIES AND PROPERTY
(Supplementing Subsection 7.13)

The Contractor, in constructing or installing facilities alongside or near sewers, drains, water or gas pipes, electric or telephone conduits, poles, sidewalks, walls, vaults or other structures shall sustain them securely in place. The Contractor shall coordinate with the officers and agents of the various utility companies and municipal departments to assure that the services of these structures are maintained. The Contractor shall also be responsible for the repair or replacement, at no additional cost to the Owner, of any damage to such structures caused by construction operations. The Contractor is responsible to leave them in the same condition as they existed prior to commencement of the work. In case of damage to utilities, the Contractor shall promptly notify the utility owner and shall, if requested by the Engineer, furnish labor and equipment to work temporarily under the utility owner's direction. Pipes or other structures damaged by the operation of the Contractor may be repaired by the Town or by the utility owner which suffers the loss. The cost of such repairs shall be borne by the Contractor, without compensation therefor.

If during construction there is an existing utility and/ or structure found to be in conflict with the proposed work under this Contract, the Contractor shall protect and maintain the services to the utilities and structures. The Engineer will, as soon as possible identify the utilities to be relocated or other such activities deemed suitable for resolution.

If live service connections are to be interrupted by excavations of any kind, the Contractor shall not break the service until new services are provided. Abandoned services shall be plugged off or otherwise made secure.

Full compensation for furnishing all labor, materials, tools, equipment and incidentals for doing all the work involved in protecting or repairing property as specified in this Section, shall be considered included in the lump sum price bid and no additional compensation will be allowed therefor.

ACCESS TO UTILITIES

The Contractor shall provide access to the Owner of any private or publicly owned utility in the event of an emergency. The Contractor shall accurately locate any structures whenever the structures are to be lowered below grade. The Contractor shall be available to access any buried structure 24 hours a day with a minimum 1 hour response time.

**WORK IN THE IMMEDIATE VICINITY OF CERTAIN UNDERGROUND
STRUCTURES AND UTILITY POLES**

For overhead connections, the Electric Company servicing the area will make the connection from the top of the riser on the utility pole to the power source. The Contractor shall supply all labor, materials and equipment to install the service connection, complete in place and in accordance with the Electric Company procedures, from the controller to and including the riser with enough wire coiled above the riser to permit the Electric Company servicing the area to make the final connection.

For underground connections, the Electric Company servicing the area will perform the actual wiring of the service connections from its power source to the sweep at the local controllers, but all steel sweeps, ducts, entrance holes into manholes, patching and all other necessary labor, materials and equipment required to install the electric service, complete in place, shall be furnished by the Contractor.

The Contractor shall pay the Electric Company servicing the area for their services rendered for the connection of overhead and underground service connections.

Before starting work at existing manholes, the Contractor shall test for gas and blow out the manholes.

TEMPORARY ACCESS TO AREA MERCHANTS AND BUSINESSES
(Supplementing Subsections 8.02 and 8.06)

The work is in a predominantly residential section of the Town of Burlington and access to all properties must be maintained at all times.

The Contractor shall provide safe and ready means of ingress and egress to all stores and shops, public and private and professional offices and any other businesses or residences in the project area, both day and night, for the duration of the project.

NOTIFICATION TO ABUTTERS

The Contractor shall hand deliver notices to abutting properties at least 24 hours before the start of construction. The notice will indicate the timing of the construction and any access restrictions or other inconveniences that may result.

The Contractor shall notify and coordinate with the Town's waste disposal contractor and school bus and transit companies when construction activities commence.

SAWCUTS

Existing pavements to remain shall be sawcut at all openings for utility work, for new or reset curb and at all joints with proposed full-depth hot mix asphalt pavement, as shown on the plans and as directed by the Engineer.

SAFETY CONTROLS FOR CONSTRUCTION OPERATIONS

(Supplementing MassDOT Subsection 850.21 and 850.61)

Safety controls for construction operations shall be done in accordance with the relevant provisions of Section 850 of the Standard Specifications, the Manual on Uniform Traffic Control Devices, the Traffic Management Plan and the following:

The providing of safety controls for construction operations shall be considered incidental to this contract and the costs for safety controls shall be included in the unit bid price for those contract items requiring such controls.

Positioning, adjusting and re-positioning of all devices such as traffic cones, high level warning devices, etc., not otherwise classified and paid for under other items in this contract, is considered incidental and no separate payment will be made.

WORK DONE BY OTHERS

Relocation and/or resetting to new grades of all private utilities, including but not limited to gas gates, made necessary by the construction of this project, will be accomplished by the respective utility companies.

The Contractor must prosecute the work efficiently and with the least possible delay. Immediately after award of the Contract, the Contractor shall confer with the owners of all utilities to assure that relocations of facilities and services may be made at times consistent with operations under this Contract.

MATERIAL REMOVED AND STACKED

The Contractor shall carefully remove, transport and stack all material that, in the opinion of the Engineer, is salvageable. The material shall be stacked at Town of Burlington DPW Facility. The Contractor shall coordinate with the Town or the Engineer to schedule drop-off time and location.

MAINTENANCE OF TRAFFIC SIGNALS

It shall be the responsibility of the Contractor to provide all labor, equipment and material required for the total maintenance and repair of all proposed traffic signal control equipment, including damage by automobile accidents until final completion and acceptance of the project, unless otherwise specified under Subsection 7.17 "Traffic Accommodation: of the Standard Specifications as amended, in which case Subsection 7.17 will govern. These provisions will apply to the signalized location included as part of this construction Contract from the date of written notice given to the Engineer that the Contractor will work on or adjacent to an existing signal until the date when the Town accepts the complete project. This written notice must be given before the Contractor may proceed with any work on the specified traffic signal location.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

For the purpose of these Special Provisions, the phrase “Traffic Signal Control Equipment” is intended to include, but is not limited to, controllers, signal housings, supporting structures, cabinet accessories and panels, wires, conduit and all other ancillary electrical equipment used for traffic control.

FINE TUNING, ADJUSTMENT, AND TESTING PERIOD

After the Contractor has finished installing the controller and all other associated signal equipment and after the Contractor has set the signal equipment to operate as specified in the Contract documents, the fine tuning, adjusting and testing period shall begin.

The Contractor shall advise the Engineer, in writing, of the date of the beginning of the fine tuning and testing period. This period shall not start until the work at the intersection is complete. During this period, the Contractor, under the direction of the Engineer, shall make necessary adjustments and tests to insure safe and efficient operation of the equipment. This period shall not last for more than 30 days and the Contract completion date has taken this testing period into consideration.

No request for final acceptance will be considered until successful completion of the testing period.

The Contractor shall notify the Engineer in writing of the starting date of the fine tuning period prior to the starting date.

FINAL INSPECTION AND ACCEPTANCE

Upon successful completion of the 30 day testing period wherein the traffic signal system has operated for 30 days without failure, the Contractor shall notify the Engineer. The Engineer will make a final inspection of the installation in the presence of the Town of Burlington and the Contractor. An inspection check will be made to ensure that all equipment, materials, installations and operations are in accordance with the construction contract, plans and specifications. Items to be checked will include, but not be limited to, traffic signal systems operation, cabinet equipment, documents (wiring diagrams, instruction manuals, parts list, warranties, grounding resistivity test report, etc.), signs, and pavement markings, and street hardware (posts, bases, housings, brackets, etc.).

The Engineer will notify the Contractor in writing of any items in which the inspection reveals that the work is incomplete, defective, or does not otherwise meet the project specifications. The Contractor shall perform the corrective actions necessary to achieve final acceptance by the Town of Burlington. These corrective actions shall be done by and at the expense of the contractor and within 15 days of the date of the inspection report, unless otherwise approved in writing by the Town.

GUARANTEE AFTER FINAL ACCEPTANCE

The Contractor shall diagnose (troubleshoot) the system and replace any part of the traffic signal system found to be defective in workmanship, material or manner of functioning within six months from date of final acceptance of all the installations under this Contract. This requirement does not affect the one-year warranty period on equipment specified in Subsection 815.20 of the Standard Specifications.

Upon the date of acceptance of the project by the Town, the Contractor shall turn over all guarantees and warranties to the Town of Burlington.

QUALIFIED ELECTRICIANS

Within 10 days after opening of bids, the low bidder shall submit a list of the Journeyman Electricians (Massachusetts License) who will perform the electrical work in this contract.

Also, the low bidder shall submit copies of each Journeyman Electrician's current Massachusetts License.

PROPERTY BOUNDS

The Contractor shall exercise due care when working around all property bounds which are to remain. Should any damage to a bound result from the actions of the Contractor, the bound shall be replaced and/or realigned by the Contractor as directed by the Engineer at no cost to the Owner.

ARCHITECTURAL ACCESS BOARD TOLERANCES

The Contractor is hereby notified that they are ultimately responsible for constructing all project elements in strict compliance with the current AAB/ADA rules, regulations and standards.

All construction elements in this project associated with sidewalks, walkways, pedestrian curb ramps and curb cuts are controlled by 521CMR – Rules and Regulations of the Architectural Access Board.

The AAB Rules and Regulations specify maximum slopes and minimum dimensions required for construction acceptance. There is no tolerance allowed for slopes greater than the maximum slope nor for dimensions less than the minimum dimensions.

Contractors shall establish grade elevations at all pedestrian curb ramp locations, and shall set transitions lengths according to the appropriate table in the Construction Standards (or to the details shown on the plans).

All pedestrian curb ramp joints and transition sections which define grade changes shall be formed, staked and checked prior to placing cement concrete. All grade changes are to be made at joints.

TOWN OF BURLINGTON STREET OPENING AND TRENCH PERMITS

The Contractor will be required to obtain all necessary permits from the Town of Burlington before the commencement of construction. All requirements, Town ordinances, laws and rules as outlined in the permits issued by the Town shall be strictly adhered to.

EXISTING CONDITIONS

Before any work commences, the Contractor shall conduct pre-existing conditions photographic documentation for each property within the project limits. The documentation shall clearly show the existing conditions of each property including but not limited to any foundations, walls, wells, driveways, fences and landscape areas. At the end of all construction activities, the Contractor shall take a post construction documentation of the same areas. The Contractor shall provide the Town with two (2) copies.

ITEM 120.1 UNCLASSIFIED EXCAVATION

The work under this item shall conform to the relevant provisions of Section 120 of the Standard Specifications for Highways and Bridges and the following:

The work shall include the disposal of existing materials shown on the drawings to be removed and reset, but which in the judgment of the Engineer are unsuitable for reuse in the proposed work and their disposal is not paid for under a separate item.

The work shall also include the excavation of material of every description regardless of the type encountered, from within the project limits as shown on the drawings and as directed by the Engineer, included with the work specified to be performed under other items of this Contract.

The Contractor is responsible for adequately protecting and supporting any utilities exposed during excavation. Any damage to a utility caused by the Contractor failing to sufficiently protect and support it will be replaced and/or repaired by the Contractor at no cost to the owner. Payment for protection and support of utilities shall not be paid separately but shall be incidental to the Contract lump sum bid price.

ITEM 141.1 TEST PIT FOR EXPLORATION

Work under this item shall conform to the relevant provisions of Section 140 of the Standard Specifications and the following:

The Contractor shall not perform any test pits exploration without the approval of the Engineer for the test pit location and size.

The Engineer may require hand excavation or vacuum explorations to avoid damaging surrounding utilities.

ITEM 191. DRIVE SAMPLE BORING

ITEM 191.10 HOLLOW STEM AUGER BORING

ITEM 191.11 CORE BORING

ITEM 193. MOBILIZATION AND DISMANTLING OF BORING EQUIPMENT

The work under these items shall conform to the relevant provisions of Section 190 of the Standard Specifications and the following:

The work under these items shall include mobilization and set-up of boring equipment, the drilling of hollow stem auger borings, drive sample borings and rock

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

core borings, the retrieval of soil samples, the visual classification of the soil, the recording of boring logs and samples, and the dismantling and transporting of the equipment to and from each site.

Hollow stem auger borings shall be taken at the locations of the proposed traffic signal mast arm foundations as shown on the plans and as directed by the Engineer. The Engineer shall be notified a minimum of 72 hours before borings are taken. Borings shall be taken to a minimum depth of 20 feet at the location of each mast arm.

Two types of samples will be required in vertical soil borings:

1. **Standard Sample**. A standard penetration test using a split spoon sampler shall be made at the ground surface and at every change in soil stratum, but the sampling intervals shall not exceed 5 feet in a continuous stratum. The auger hole shall terminate at the required bottom elevation and a split spoon sample shall be taken at the bottom of the hole.
2. **Supplement Sample**. A volume sample shall be taken at 5-foot intervals to classify the subsurface soils with respect to grain size and visual classification as required. Each sample shall consist of the remainder of the spoon sample and shall be contained in quart jars appropriately labeled.

The purpose of this method along with its sampling procedure is to determine the visual properties, arrangement, and thickness of the various soil strata as they exist in the ground. The elevations/depths at which any change in stratification occurs shall be located and recorded on the log by the driller. Detection of stratum changes should be made by careful observation of the soil as it exists in the augered hole and by the rate of penetration of the auger during drilling.

The auger casing I.D. shall be a minimum of 2-3/4 inches for all holes in which split spoon samples are required. The O.D. shall be a maximum of 7 inches to limit the size of the resulting hole.

Supplement Samples

The quart jar samples shall have positive identification of the contents by typewritten glued-on label.

The following information shall be shown:

1. Name and address of boring contractor
2. Date sample was taken
3. Location and name of project.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

4. Location of borehole by station and offset or identifying number of borehole, if so identified on the plan.
5. Depth below ground surface at which sample was obtained and recorded blow counts of 6 inches of penetration of the sampler.

Upon completion of all borings, the Contractor shall submit two copies of the typewritten boring logs to the Engineer and deliver the jarred samples plus two copies of the typewritten logs to Vanasse Hangen Brustlin, Inc., Watertown, Massachusetts.

Obstructions

Obstructions other than ledge shall be considered in accordance with Sub-section 190.60E of the Standard Specifications. The actual location of the additional boring will be specified by the Engineer. When ledge is encountered, a rock core boring will be made in accordance with Sub-section 190.63 of the Standard Specifications.

Rock Core

If rock is encountered at an elevation above the specified highest bottom elevation, then a rock core boring will be made in accordance with Sub-section 190.63 of the Standard Specification. The core hole shall be large enough to accommodate the required auger casing so that sampling may be continued past the rock obstruction. The minimum cored depth shall be 10 feet.

Practical Refusal

Practical refusal of the sample spoon or "refusal" is as defined by Sub-section 190.60F of the Standard Specifications.

Due to the size of the resulting auger hole, it is particularly important that upon completion, all borings shall be backfilled with clean, well-graded sand and tamped to fill all voids created during the augering procedure.

Advancing the Boring for Soil Sampling

As the boring is advanced, care shall be taken to note and record the depth where wet soil is encountered if this should occur.

If groundwater is encountered, then the water level in the hollow stem shall be maintained at the top of the casing at all times during the sampling operation to avoid unequal hydrostatic pressure that could result in blow-in of fine-granular soils and inaccurate blow counts.

In each boring the driller shall record the water level prior to backfilling and whenever possible, prior to the start of each day's work.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

Each boring shall be advanced by using a hollow stem auger with cutting head and center rod and plug assembly. The hollow stem auger will advance and case the hole simultaneously to the required sampling levels. The center rod and plug assembly is held in place by the cap and inside drill rod connecting the auger and its assembly to the rotating spindle on the drilling machine to prevent soil from entering the mouth of the auger. Upon reaching the sampling level, the plug is to be retreated by withdrawing the center rod to permit lowering of the sampler through the auger.

The sample shall be obtained by driving the sampler 18 inches into the undisturbed material below the bottom of the auger. The sampling and handling procedure shall be as specified under Sub-section 190.61 of the Standard Specifications.

After the sampling operations are completed and the sampler has been retracted, the plug is re- inserted and held in place by the center rod; another auger section is connected to the first, together with one additional center rod section to secure the plug to the cap and the hole is advanced.

This procedure shall be repeated until the required bottom elevation is reached. The auger shall be stopped at any depth level to allow normal sampling practices upon request by the Engineer.

If, in the judgment of the Engineer, the borehole cannot be advanced by the hollow stem auger method due to the material encountered (with the exception of bedrock) and every attempt has been made by the driller to complete the boring using the conventionally cased, drive sample, wash boring method as specified in Section 190 of the Standard Specifications, then the borehole shall be cored.

ITEM 472. TEMPORARY ASPHALT PATCHING

The work under this item shall conform to the relevant provisions of Section 472 of the Standard Specifications and the following:

The work shall include placement of hot mix asphalt for temporary pedestrian and vehicular access as well as traffic management and maintenance.

The Contractor is advised that this material will have to be placed primarily by hand methods.

ITEM 580. CURB REMOVED AND RESET

ITEM 581. CURB INLET REMOVED AND RESET

ITEM 582. CURB CORNER REMOVED AND RESET

ITEM 594. CURB REMOVED AND DISCARDED

ITEM 595. CURB INLET REMOVED AND DISCARDED

ITEM 596. CURB CORNER REMOVED AND DISCARDED

Work under these Items shall conform to the relevant provisions of Section 500 of the Standard Specifications and the following:

The Contractor shall only reset existing curbing that has been approved by the Engineer for re-use. All unsuitable pieces shall be legally disposed of off-site.

Granite curb not required to be removed and reset, shall become the property of the Contractor and shall be removed from the site during the construction period and legally disposed of off-site. Curved granite curb with different radius than the proposed curb are unsuitable for reuse. Damaged curb stones are unsuitable for reuse. All stones to be reused which have damaged ends shall be sawcut square with the top plane so when stones are placed end to end the joint opening does not exceed one half inch.

Reset curb shall be reset contiguously. New curb stones shall be installed contiguously. Alternating new and old stones shall not be permitted.

The Contractor is advised that granite curb removed may be reset elsewhere at a different location within the Contract limits and all costs incurred for handling and transporting existing curb shall be included in the Contract lump sum bid price.

ITEM 697.1 SILT SACK

Work under this item shall conform to the relevant provisions of Sections 227 and 670 of the Standard Specifications and the following:

The work under this item includes the furnishing, installation, maintenance, and removal of a reusable fabric sack to be installed in drainage structures for the protection of wetlands and other resource areas and the prevention of silt and sediment from the construction site from entering the storm water collection system. Devices shall be ACF Environmental (800)-448-3636; Reed & Graham, Inc. Geosynthetics (888)-381-0800; The BMP Store (800)-644-9223; or approved equal.

CONSTRUCTION

Silt sacks shall be installed in retained all catch basins and drop inlets within the project limits and as required by the Resident Engineer.

The silt sack shall be as manufactured to fit the opening of the drainage structure under regular flow conditions and shall be mounted under the grate. The insert shall be secured

from the surface such that the grate can be removed without the insert discharging into the structure. The filter material shall be installed and maintained in accordance with the manufacturer's written literature and as directed by the Engineer.

Silt sacks shall remain in place until the placement of the pavement overlay or top course and the graded areas have become permanently stabilized by vegetative growth. All materials used for the filter fabric will become the property of the Contractor and shall be removed from the site.

The Contractor shall inspect the condition of silt sacks after each rainstorm and during major rain events. Silt sacks shall be cleaned periodically to remove and disposed of accumulated debris as required. Silt sacks, which become damaged during construction operations, shall be repaired or replaced immediately at no additional cost to the City.

When emptying the silt sack, the Contractor shall take all due care to prevent sediment from entering the structure. Any silt or other debris found in the drainage system at the end of construction shall be removed at the Contractor's expense. The silt and sediment from the silt sack shall be legally disposed of offsite. Under no condition shall silt and sediment from the insert be deposited on site and used in construction.

All curb openings shall be blocked to prevent stormwater from bypassing the device.

All debris accumulated in silt sacks shall be handled and disposed of as specified in Section 227 of the Standard Specifications

ITEM 701.05 CEMENT CONCRETE SIDEWALK MUNICIPAL STANDARD

**ITEM 701.15 CEMENT CONCRETE SIDEWALK AT DRIVEWAYS
MUNICIPAL STANDARD**

**ITEM 701.25 CEMENT CONCRETE PEDESTRIAN CURB RAMP MUNICIPAL
STANDARD**

The work under these items shall conform to the relevant provisions of Section 701 of the MassDOT Standard Specifications, the Town of Burlington Standards and the following:

All cement concrete sidewalk shall contain fibermesh fibers. Fibermesh fibers (100% virgin polypropylene, collated, fibrillated fibers) at a rate of 1.5 lb. per cubic yard of concrete shall be added for reinforcement. Installation shall be per manufacturers recommendations.

The depths of concrete shall be 6 inches in driveways and pedestrian curb ramps to meet the Town of Burlington standards.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

Premolded joint filler shall be installed 30 feet on center and used for boxing out street furniture (utility poles, hydrants, light poles, etc.) in sidewalk.

Detectable Tactile warning surface shall conform to the requirements of MassDOT as shown on the 2017 Construction Standard Details (Standard Drawing 107.6.5) and shall be “red” in color.

No separate payment will be made for the detectable warning panels, but all costs in connection therewith shall be included in the Contract lump sum bid price.

ITEM 707.8 STEEL BOLLARD

Work under this Item shall consist of furnishing and installing concrete filled steel pipe bollards as shown on the drawings and as specified herein including all labor, materials and equipment necessary to finish the work complete in place.

MATERIALS

ROUND STEEL PIPE – The pipes shall be round 4-inch diameter seamless steel conforming to ASTM Designation A53, with schedule 40 minimum wall thickness as shown on the plans. The length of the pipes shall be as called for on the detail.

GALVANIZING AND PAINT – Galvanizing and painting shall conform to the relevant provisions of section 975. Paint shall be Safety Yellow.

CEMENT CONCRETE – Cement concrete for footings and filler shall conform to Subsection M4.02.00 of the Standard Specifications for Highways and Bridges.

CONCRETE FOOTINGS AND FILLER – All bollards shall be set vertically plumb and securely anchored in cement concrete footings as called for on the detail.

ITEM 804.3 3-INCH ELECTRICAL CONDUIT TYPE NM PLASTIC (UL)

The work under this item shall conform to the relevant provisions of Section 801 of the Standard Specifications and the following:

The work shall include the furnishing and installation of 3-inch non-metallic conduit for the traffic signal system in accordance with the plans and as directed by the Engineer.

The conduit material shall be Schedule 80 polyvinyl chloride (PVC) plastic conduit.

The linear footage of conduit estimated under this Item is not guaranteed by the Engineer; it may be increased or decreased by the Engineer depending upon actual conditions encountered as provided for in Section 4.06 of the Standard Specifications.

Where new conduits are installed in existing grass areas outside the limits of grading, the work shall include the placement of a minimum of 4 inches of topsoil and sod to restore the disturbed areas to their original condition, unless otherwise directed by the Engineer. No separate payment will be made for this work, but all costs in connection therewith shall be included in the Contract lump sum bid price.

Where conduit is installed in existing sidewalk or paved median areas to remain, the work shall include replacement of the gravel base material and the surface pavement to match preconstruction conditions unless otherwise noted on the plans. No separate payment will be made for this work, but all costs in connection therewith shall be included in the Contract lump sum bid price.

Metallic warning tape shall be placed above the conduit as shown on the Construction Details. A ¾-inch polypropylene pull rope shall be installed in all conduits.

ITEM 811.31 PULL BOX 12 x 12 INCHES – SD2.031

The work under this item shall conform to the relevant provisions of Section 801 of the Standard Specifications and the following:

The work shall include the furnishing and installation of pull boxes, frames, and covers for the traffic signal systems in accordance with the plans and as directed by the Engineer.

Pull boxes associated with traffic signals shall have “TRAFFIC” embossed on the cover.

ITEM 815.1 TRAFFIC CONTROL SIGNAL LOCATION NO. 1

The work under this Item shall conform to the relevant provisions of Section 800 of the Standard Specifications, the 2009 Manual on Uniform Traffic Control Devices (MUTCD), and the following:

The work shall include the furnishing and installation of part or all of the following items: local traffic signal controller; cabinet and foundation; mast arm assemblies with anchor bolts and foundations; signal posts and foundations; signal heads; backplates; pedestrian signals with countdown timers; audible pedestrian signal (APS) push buttons with signs; single-point vehicle detection; emergency vehicle preemption; Field Monitoring Unit; all cable and wiring; ground rods, equipment grounding and bonding; and all other equipment, materials and incidental costs necessary to provide

complete, fully operational traffic control signal system as specific herein and as shown on the plans. The location is as follows:

- Winn Street at Mountain Road

The Contractor shall integrate the above intersection into the existing cloud-based Town of Burlington Central Management System (CMS) Trafficware ATMS.NOW. The Contractor shall include any software/hardware to allow for this integration including but not limited to cabling and licenses.

Lists of the major traffic signal items required at this location is included on the plans.

Shop Drawings

Within 30 days following execution of the Contract, the Contractor shall submit shop drawings for signal supports, a list of equipment, and manufacturer's equipment specifications to the Engineer in accordance with the relevant provisions of Section 815.20.

No work shall be commenced by the Contractor until approval of the shop drawings and manufacturer's data has been received in writing from the Engineer. Approval of these drawings will be general in character and shall not relieve the Contractor from the responsibility of, or the necessity of, furnishing materials and workmanship conforming to the plans and specifications.

The Design Consultant shall return the shop drawings within 15 days from the date of receipt from the Engineer.

The Contractor shall deliver to the Engineer a certificate of compliance with the manufacturer for all materials purchased from the manufacturer.

Signal Turn-on

Prior to initial turn-on of the new signal, equipment, signal displays, and vehicle detection as shown on the plans and called for in these special provisions, shall be installed and operable.

Applicable signs and pavement makings shall also be in place when the signals are put into operation.

Service Connection

The service connection shown on the plans is approximate only. The Contractor shall determine exact location from the servicing utility, arrange to complete the service connection, and be responsible for all charges incidental thereto.

The respective utility company is responsible for making the connection from the respective riser to the overhead wires.

Testing of Grounding System

The Contractor shall perform testing of the equipment grounding system in the presence of the Engineer in accordance with MassDOT Standard Specifications.

Flashing Operation

Changes from automatic flashing to stop-and-go operation and from stop-and-go to automatic flashing operation shall occur as set forth in the MUTCD.

Traffic Signal Equipment

The traffic signal controller unit (CU) malfunction management units (MMU), and all other ancillary traffic signal control components included in the traffic control cabinet shall comply with the National Electrical Manufacturers Association (NEMA) Standard No. TS 2-2003 (R2008) v02.06 and Amendment 4-2012 Traffic Controller Assemblies with National Transportation Communications for ITS Protocol (NTCIP) Requirements.

Traffic Signal Controller

The traffic controller supplied shall conform to Section 3 “Controller Units” of the NEMA TS 2 Standard. The traffic controller shall be supplied in a TS 2 Type 1 Configuration as required in the list of major traffic signal items included on the plans.

The controller unit shall utilize an interface conforming to Subsection 3.3 of the NEMA TS 2 Standard. The controller unit shall utilize an input/output interface conforming to the requirements of Paragraph 3.3.1 for all input/output functions with the Terminals and Facilities (TF), Malfunction Management Unit (MMU), detector rack assemblies and auxiliary devices. The controller unit shall also meet the requirements of Paragraph 3.3.6 of the NEMA TS 2 Standard.

The controller unit shall be supplied with Port 1, Port 2, and Port 3 as defined by the requirements of Subsections 3.3.1, 3.3.2, and 3.3.3, respectively. It shall include a temperature compensated, 8 line by 40 character display with LED backlight. The controller operating system (OS) shall be Linux and contain a Flash File System to allow for controller software upgrades.

The controller shall support 1/10th second high-resolution data logging which provides detailed operational information allowing for the generation of enhanced performance metrics. This would include construction of Purdue Coordination Diagrams, time space diagrams and measures of effectiveness.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

The controller unit shall meet the approval of the Town. Note: As part of the shop drawing submission the Contractor shall provide written approval of the controller unit from the Town.

Malfunction Management Unit

The malfunction management unit (MMU) shall comply with Section 4 of the NEMA TS 2 standard, as defined by amendment 4-2012. The MMU shall be supplied as a NEMA MMU designation “MMU2” as defined in table 4-1 of the NEMA standards. The MMU shall operate as either a Type 16 with 16 channels (8 vehicle, 4 pedestrian and 4 overlap) or a Type 12 with 12 channels (8 vehicle, 4 overlap). The MMU supplied shall be configured to operate as a Type 16 unit. The MMU shall be supplied with an Ethernet port and shall support Ethernet communications. The Malfunction Management Unit shall have the functionality to support MUTCD’s flashing yellow operations.

The MMU in either the Type 16 or Type 12 configuration shall operate in a NEMA TS 2 Type 1 cabinet, a NEMA TS 2 Type 2 cabinet, or a NEMA TS 1 cabinet without loss of functionality.

Field Monitoring Units (FMU)

Under this item the Contractor shall consist of furnishing and installing a Field Monitoring Unit (FMU) and software, as well as all needed accessories required for a full and complete installation, including but not limited to power adapters, Ethernet cables, and interface cables, as described herein.

MATERIALS: The materials for this work shall conform to the following requirements:

1. The FMU shall operate independent of the brand/type of intersection controller deployed in the traffic cabinets.
2. The FMU shall conform to the following requirements:
 - 2.1 The FMU shall function correctly between -34 degrees C and +74 degrees C.
 - 2.2 The maximum size of the FMU shall be 19" x 7,455" by 1.719" (1U) and shall be suitable for placing in a traffic cabinet.
 - 2.3 The FMU shall be provided with appropriately rated connectors that allows the FMU to be exchanged by unplugging connectors, without tools.
 - 2.4 The FMU shall monitor and log all traffic controller and cabinet faults and or alarms.
 - 2.5 The FMU shall be wired directly to the traffic cabinet for all connections power and data.

- 2.6 The FMU shall have an internal cellular modem running at 4G LTE.
- 2.6.1 The Cellular modem shall be designed to be replaced / upgraded to 5G service when available.
- 2.7 The FMU shall have two or more remotely switchable 120 Volt AC outlets.
- 2.8 The FMU shall incorporate an integrated GPS and cell modem.
- 2.9 The FMU and or GPS antenna shall be connected to the traffic signal to provide for clock time sync pulse.
- 2.10 The configuration of the FMU shall be accomplished by accessing the internal web server with a browser. It shall be possible to configure the FMU without any special software.
- 2.11 The FMU shall be powered via a standard 120V input power.
- 2.12 The FMU shall allow for the routing of the controller configuration packets to and from the controller (either by Ethernet or serial communications) for any type of controller utilized by the Town. In this way it shall be possible to configure the controller and utilize the controller specific software to interrogate the controller, and the FMU shall provide the communications pipe which allows this to be accomplished.
- 2.13 The FMU shall allow the Town to live stream the video detection cameras via the FMU internal cellular modem and the FMU manufacturers cloud hosted website. There shall be no cellular over charges to the Town for this feature.
- 2.14 The FMU shall allow and be configured to provide access to the traffic signal controller front panel display via the FMU manufacturers cloud hosted website.
- 2.15 The FMU shall be configured to broadcast the traffic controller SPaT messages via the FMU mobile application.
- 2.16 The FMU shall, within the size limitations above, include a battery and battery charging/monitoring circuit, to allow the FMU to function correctly even when all power to the intersection has failed. The battery shall continue to power the FMU for a minimum of 5 hours after all power has failed to the intersection.
- 2.17 The FMU shall incorporate an integrated GPS which will allow the FMU to geo- locate itself on the FMU management software map, without configuration.
- 2.18 The FMU shall operate without requiring a static IP address.
The only configuration required at the FMU is to enter the URL of where the FMU management software is hosted.

- 2.19 In the event that the cell service is interrupted or is not available, the FMU shall store any events that occur in internal memory and forward these events automatically to the FMU management software when the cell service is restored. In this way, a complete record of events at the device can be maintained even if cell service is interrupted for a period. The system will store 5000 events.
- 2.20 The FMU shall utilize HTTPS protocols, and XML data structures, for communication with the FMU management software. In this way the data will be open for future expansion and competition. The use of secret proprietary protocols is not permitted.
- 2.21 The FMU shall be a 1U 19" rack mount device, with all connections on the rear, and LED indicators, power switches and selector switches on the front.
- 2.22 The FMU shall include Ethernet communications via four Ethernet Ports with RJ45 connectors.
- 2.23 The FMU shall be powder coated aluminum enclosures.
- 2.24 The FMU shall include weatherproof antennas.
- 2.25 The FMU shall include the ability to remotely cycle power to the outlets on the back of the FMU. In this way it shall be possible to cycle power to ancillary connected equipment such as network switches, cameras and similar equipment.
- 2.26 The user interface shall display the status of the outlets and provide confirmation via an associated input whether the sockets are energized or not.

3. Map Display FMU Management Software

- 3.1 The FMU shall include a scrollable, zoomable map display, with the intersections and other monitored devices shown as representative icons on the map. The map shall include the ability to see the intersections using Google Streetview.
- 3.2 The alarm status of the intersection shall be clearly indicated on the icon on the map, so that the user can see at a glance which intersections are in alarm.
- 3.3 The map display shall also include a list of intersections, with the number and priority of alarms indicated on the list. Intersections in high priority alarm shall be moved to the top of the list, followed by medium priority, low priority and then finally by intersections not in alarm.
- 3.4 The icons shall change to be able to clearly indicate if an intersection is offline.

- 3.5 Clicking on the icon on the map shall expose a box with the current parameters of the intersection shown.
- 3.6 The default map display position and zoom shall be configurable by user, so that the user's view will default to show the intersections that the user is responsible for managing.
- 3.7 The map view shall have the ability to show Google traffic overlays on the map.

4. Intersection Detail Display FMU Management Software

- 4.1 It shall be possible to drill down, either from the map icon or from the list, to a device level detail for the intersection, which as a minimum shall display the following parameters:
 - 4.1.1 The alarm status, with priority indicated, and a text description of the alarm (if an alarm is present for this device).
 - 4.1.2 The time since the last communication with the device
 - 4.1.3 The following parameters (real time now values, minimum for the day values, maximum for the day values, and average for the day values)
 - 4.1.3.1 The AC mains voltage (value)
 - 4.1.3.2 The battery back-up voltage (value)
 - 4.1.3.3 The cabinet temperature (value)
 - 4.1.3.4 The cabinet humidity (value)
 - 4.1.3.5 The presence of AC power (OK or Fail)
 - 4.1.3.6 The flashing status of the intersection (OK or Flashing)
 - 4.1.3.7 Stop Time status (OK or Stop Time Active)
 - 4.1.3.8 The cabinet door status (Open or Closed)
 - 4.1.3.9 The intersection fan status (Fan On or Fan off)
 - 4.1.4 It shall be possible to view graphs of each of the value parameters in graphical form, over the recent two-week period. This includes real time graphs of:
 - 4.1.4.1 The AC mains voltage
 - 4.1.4.2 The battery back-up voltage
 - 4.1.4.3 The cabinet temperature

4.1.4.4 The cabinet humidity

5. Diagnostics and Log Display FMU Management Software

- 5.1 From the device level detail within the FMU management software, it shall be possible to drill down to get the raw data; the error logs; and the communications logs to allow a technician to fault-find problems.
- 5.2 It shall be possible to filter the logs by Device; by Device Type and/or by Group as well as between dates.
- 5.3 It shall be possible to print these selected logs to a local printer or a PDF file.
- 5.4 It shall be possible to export these logs to Excel on the local computer for further analysis.

6. Alarms FMU Management Software

- 6.1 The FMU management software shall have a comprehensive alarm generation capability
- 6.2 It shall be possible to configure alarms to be generated on any parameter becoming out of tolerance, including analog values, digital values and enumerated values.
- 6.3 Alarms shall be configurable to be of Low, High or Critical Priority.
- 6.4 The alarm priority shall be displayed throughout the FMU management software, on all displays, using color codes such as red-critical; yellow – high; and amber-low to indicate the priority of the alarm.
- 6.5 The current active alarms shall be accessible for view via an expandable window, to see which alarms are active and when the alarm occurred. The highest priority alarms shall rise to the top of the list.

7. Alerts FMU Management Software

- 7.1 The FMU management software shall have comprehensive alerting capability, to enable the response personnel to be notified when an abnormal situation has occurred.
- 7.2 It shall be possible to configure alerts to one or more personnel for each alarm. This will cause, as selected, an SMS and/or an email to be sent to the person when an alarm occurs.
- 7.3 The alert shall be configurable to optionally send via email and/or via SMS a message when an alarm clears.
- 7.4 The intention is that the FMU management software provides the alerts to the user in near real time. The SMS and email shall be issued within 30 seconds of the occurrence of event which results in an alert being issued.

8. Hosting and Connectivity and Service FMU / FMU Management Software

8.1 The Contractor shall supply the FMU with the FMU manufacturers 10-year Connectivity and Service, as part of the purchase price. The Connectivity and Service agreement shall include at a minimum:

- 8.1.1 Cellular Connectivity
- 8.1.2 Upgrade the cellular modem if the technology is not supported by the cellular networks.
- 8.1.3 Telephone and email support
- 8.1.4 No cellular overage charges
- 8.1.5 Extended warranty on the hardware for the period of the Connectivity and Service Agreement
- 8.1.6 Over-the-air software updates
- 8.1.7 Over-the-air security updates
- 8.1.8 Future Connected Vehicles Service

Single-Point Video System

The Contractor shall provide and install a Single-Point Video Detection (SPVD) System at the project intersection as shown on the plans and these special provisions. The SPVD system shall include a single ultra-wide angle lens camera, video processor unit, detection algorithms, all cables, connections, mounting hardware, application software, and accessories required by the manufacturer for proper operation of the system, including but not limited to surge protection devices. No additional hardware, software items and/or subscription fees/ costs shall be needed/ allowed to satisfy the requirements in these specifications for the life of the project.

The SPVD system shall detect and monitor vehicles on approach roadways utilizing advanced, omni-directional, vehicle tracking algorithms along with three-dimensional vehicle modeling to supply accurate and consistent stop line detection. The SPVD system shall be able to count vehicles and store this information on a database that can be retrieved by the Town at a later date. The SPVD system shall include software for counting vehicles, including turning movement counts by 15-minute time intervals and be capable of storing said data.

The SPVD system shall include all necessary software and hardware to allow the end user to program, setup, and/or modify detection zones within the video camera image. The system software shall be an installable client configuration software, and not be a web-based client program.

One pointing device and one color monitor within the controller cabinet for future viewing of the camera images shall be supplied by the Contractor. The Contractor shall also supply any necessary cables, interface devices and software for monitoring video detection via laptop computers.

The camera shall be mounted at the intersection, as shown on the plan or as directed by The Engineer,

At a minimum, the SPVD shall meet the following requirements:

Camera

- Power: 48 VDC, single burial grade CAT 5e cable
- Operating Temp: -35C to +60C
- Humidity: Up to 100%
- Dimensions: 10" diameter x 9"
- Weight: less than 11 lbs.
- The camera shall include an ultra-wide-angle lens.
- The camera shall include a heater to prevent the formation of ice and condensation.
- The camera, when properly installed and configured, shall be able to concurrently observe at least 5 lanes of traffic per approach. The camera shall be able to concurrently observe more than one approach.

Video Processor Unit

- Power: 120-240 VAC, requiring 150 watts or less.
- Operating Temp: -34C to +74C
- Humidity: Up to 95% non-condensing
- Dimensions: 12.25" wide x 11.25" depth x 5" high
- Weight: 12 lbs.
- Enclosure: Rack mount in traffic cabinet The video processor unit shall save configurations and zone plans locally to maintain operation with or without monitoring equipment connected. The video processor unit shall be designed to function dependably in the adverse environment found in the typical roadside traffic cabinet.
- The video processor unit shall include at least 24 detector outputs.
- The video processor unit shall include an SDLC connection for TS2 type controllers.
- The video processor unit shall include a USB on the front surface for simple data collection on non-network systems. The video processor unit shall include both LAN and WAN RJ-45 interface ports on the front surface of the unit.

Application Software

- The application software shall support the creation and modification of at least twenty-four
- (24) polygonal detection zones within the graphical user interface.
 - The application software will show images of the detection zones superimposed on the video image of traffic.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

- The application software shall support the assignment of a detector output(s) to each zone. These assignments can be modified at any time through the software.
- The application software shall support direction of travel assignment within detection zones.
- The vehicle detection zone shall not activate for objects traveling any direction other than the one specified for detection. Cross-street and wrong way traffic shall not cause detection.
- The application software shall change the color of the zone within the graphical user interface as vehicles enter or exit a detection zone, changing its occupancy status. This will be required for real-time or historical monitoring and may be turned on or off by the user at any time.
- The application software shall provide visual indication of the light state for each zone within the graphical user interface.
- The application software shall feature the ability to digitally pan, tilt, and zoom within the camera's field of view without movement of the camera.
- The application software shall maintain a database of current and historical traffic data and allow for the user to run reports against this data to include traffic counts, turn movements, speed, and classification at a minimum.
- The application software shall feature the ability to mask objects that occlude the camera field of view and/or disrupt the camera automatic gain and exposure control.
- The application software shall feature an optional reporting interface offering point and click reporting for turning movement counts and vehicle classification.

The Contractor shall provide software that enables a technician to test all features and functions of the SPVD system, and to perform all set-up procedures. This software shall be delivered on a CD so that it can be installed on other tablets/laptops. The owner shall have the right to make and use an unlimited number of copies of this software.

The SPVD system shall be installed in accordance with the manufacturer's recommended procedure for installation.

The SPVD system shall be installed by factory certified installers and as recommended by the manufacturer and documented in installation materials provided by the manufacturer. Proof of the factory certification shall be provided. Installation includes connecting the SPVD to the traffic signal controller and power supply in the associated controller cabinet assembly. When the setup is complete and the SPVD system is ready for operation, the values of all parameters that were set during the process shall be delivered to the Engineer in printed and computer-readable form. All equipment, such as software, laptop computer, tools and cables, needed for setup work shall be provided by the Contractor.

The Contractor shall be responsible for the proper programming of the SPVD, orientation of the SPVD, and all other work necessary to provide a complete operating system. The Contractor may be required to field adjust the location of the SPVD system in the presence of the Engineer to properly detect approaching vehicles.

The cabinet documentation (box prints) shall show all wiring between the SPVD system and the controller cabinets.

Data Stick/ Drive

The Contractor shall supply A USB stick or drive used for collecting and synchronizing data and site configurations. The USB stick or drive must be NTFS-formatted and have enough available space to allow data to be synchronized.

Warranty -The supplier shall provide a three-year warranty on the SPVD system following installation and warranty registration. The camera shall include an additional warranty to require no aiming or focusing for a period of five years. During the warranty period, technical support shall be available from the supplier via telephone within 4 hours of the time a call is made by a user, and this support shall be available from factory-certified personnel or factory-certified installers. During the warranty period, updates to SPVD software shall be available from the supplier without charge.

Video BIU Module

The Video BIU module shall be compatible with NEMA TS2 detector card racks and shall meet the following requirements:

- Shall support 64 detector inputs.
- Shall select TS-2 detector BIUs to emulate and operate up to 4 BIUs simultaneously.
- Shall provide SDLC interface for video processing cards.
- Allow for multiple detection zones to be assigned to the same camera.

Detector Rack Assemblies

The detector rack assemblies shall conform to Paragraph 5.3.4 of the NEMA TS 2 Standard. The detector rack assembly shall be supplied in a Type 2 configuration as defined in Table 5-9 of the NEMA TS 2 Standard.

Cabinet Power Supply

Separate power supply shall be supplied and installed in the TS 2 cabinet. As a minimum, the power supply shall meet all requirements of Paragraph 5.3.5 of the

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

NEMA TS 2 Standard. The unit shall be AC line powered and provide regulated DC power, unregulated AC power, a line frequency reference for the load switches and other auxiliary cabinet equipment as required.

The power supply shall be shelf or rack mounted.

The unit shall contain four LED indicators on the front panel to indicate the four outputs;

1. + 12 VDC +/- 1 VDC @ 2.0 amps,
2. + 24 VDC +/- 2 VDC @ 2.0 amps,
3. 12 VAC @ 250 milliamps, and
4. 60 Hz line frequency reference.

A test point terminal shall also be located on the unit front panel for + 24VDC and logic ground testing.

Surge Suppression

The Contractor shall supply and install surge suppression in the traffic controller cabinet in accordance with the manufacturer's recommendations. At a minimum surge suppression shall be provided for, video detection, power service, and emergency preemption.

Load Switches

Load switches shall comply with Subsection 6.2 of the NEMA TS 2 standard. All load switches shall utilize optically isolated encapsulated modular solid-state relays. Discrete components on circuit boards are not acceptable.

Load switch indicator lights shall be LED-type and wired on the input side of the device.

Flasher

Flashers shall comply with Subsection 6.3 of the NEMA TS 2 standard and be equipped with two output indicator lights which will show flashing power out to the cabinet assembly.

Flash Transfer Relays

Flash transfer relays shall comply with Subsection 6.4 of the NEMA TS 2 standard.

The field electrical loading for flash operation shall be wired through the transfer relays such that the load on the 2-circuit flasher is as balanced as possible within the limitations of the signal phasing.

Traffic Controller Cabinet

Controller cabinet shall conform to the NEMA TS 2 Standards, Section 7. Cabinet sizes shall be as indicated on the plans and as shown below.

TS 2 Type 1 Configuration Table

Item Number	NEMA TS 2 Cabinet Size	Nominal Cabinet Size (HxWxD)*	Config- uration Type Table 5-2	Load Switch Positions	Flash Transfer Relays	BIUs Required	Detector Rack Type Table 5-9	MMU2 (Channels)
815.1	6	52x44x24	3	12	6	4	2	16 Channel

* Approximate cabinet dimensions are provided in inches.

The cabinet shall be made of aluminum.

Where applicable, the cabinet shall be installed with the door opening positioned to allow general observation of the flow of traffic and the inside of the cabinet at the same time.

The cabinet shall be furnished with a minimum of two moveable shelves suitable for placing the controller, MMU, detector racks, network equipment, or any other required equipment. A slide- out document tray shall be mounted below the bottom shelf. The tray shall be of sufficient size to hold cabinet wiring diagrams and two manuals. The tray shall operate by sliding out on nylon rollers or ball bearings and opening a hinged cover to remove documents.

The closed cover shall provide a suitable support for resting documents or a laptop computer. All cables shall be tied away to allow the tray to be opened and closed smoothly without any obstructions.

Controller cabinet foundation shall not obstruct a sidewalk or crosswalk so that passage by physically challenged persons is impaired.

GFI Duplex Outlet

The Contractor shall supply and install a second separate GFI protected duplex outlet in the controller cabinet and mounted on the side wall of the cabinets for servicing other devices.

Manual Override (Police Control Button)

The Contractor shall provide and install a fully wired, environmentally sealed momentary contact (push button) handheld switch shall be supplied with a retractable cord that will extend approximately 6 feet.

Provision shall be made for neat cord and handheld switch storage within the police panel. This handheld switch and retractable cord shall be permanently wired and shall not be plugged-in removable.

Manual operation of the controller shall provide the same color sequence as was programmed for the automatic operation. The duration of all intervals, except the yellow vehicle and red vehicle clearance interval, shall be controlled by operation of the remote manual control switch. Duration of the yellow interval and red clearance interval shall be the time specified to be programmed in the controller unit.

Bus Interface Units

The Bus Interface Units (BIU) shall comply with Section 8 of the NEMA TS 2 Standard. The BIU shall be fully interchangeable with any other manufacturer's unit and interchangeable in a NEMA TS 2 Type 2 cabinet assembly.

At a minimum the BIU shall perform the interface function between port 1 at the controller unit, the malfunction management unit (MMU), the detector rack assembly (video detection), and the terminal facilities. The cabinets shall be supplied with the appropriate number of BIUs required to provide an operating traffic control signal according to the plans and these specifications.

As a minimum, two LED indicators shall be provided on the BIU front panel. One indicator shall serve a dual use; as a power on indication and as a diagnostic indicator for proper operation of the device. The second indicator shall serve as a transmit indicator illuminating each time data is transmitted.

Spare Equipment

The Contractor shall provide the following spare signal equipment in the proposed traffic signal controller cabinet:

- One TS2, Type 1 Controller Unit with Linux operating system, per Town Standards
- Single point detection system (1 Camera)
- A full complement of load switches to accommodate each available position of the back panel.
- A full complement of flash transfer relays to accommodate each available position of the back panel.
- Two (2) Bus Interface Units.

- A 25 foot Ethernet cable

Emergency Preemption

The emergency vehicle preemption system shall be Global Traffic Technologies, LLC (GTT) OPTICOM Priority Control System Model 700 series, or approved equivalent, installed in the same cabinet as the controller.

The emergency vehicle preemption control system shall consist of a data-encoded phase selector to be installed within the traffic control cabinet in the detector racks. This unit will serve to validate, identify, classify, and record the signal from the optical detectors located on support structures at the intersection.

Upon receiving a valid signal from the detector, the phase selector shall generate a preempt call to the controller initiating a preemption operation as shown on the plans.

The optical detector shall be single input, single output unit used to control one approach. The optical detector shall be OPTICOM model 711 series or approved equal. All traffic signal installations shall be supplied with a minimum of two optical detectors unless otherwise noted in the major items list.

The phase selector shall be a rack-mounted plug-in four channel dual priority device OPTICOM model 754 series or approved equal. The phase selector shall plug into an empty slot in the detector rack. Programming the phase selector shall be via a PC-based computer utilizing unit specific software. One copy of preemption programming software on a CD shall be supplied and licensed to the Town of Burlington. A hard copy of final programming data shall be left in the control cabinet. A complete set of interface cables for phase selector to laptop connection shall be supplied in the cabinet.

The Contractor shall install a confirmation strobe at the traffic signal location as shown on the plans. The confirmation strobe shall serve to validate to the driver of the emergency vehicle that the traffic signal has recognized the preemption call and will initiate the proper preemption sequence. The confirmation strobe shall be a white lens Whelen IS3 series or equivalent.

The Contractor shall be responsible for the proper programming of the phase selector, orientation of the optical detectors, and all other work necessary to provide complete and operating emergency vehicle preemption systems. The Contractor may be required to field adjust the location of the optical detectors in the presence of the Engineer to properly detect preemption calls from approaching vehicles. Upon final inspection and testing, any discrepancies or failures to properly preempt the traffic signals will necessitate a complete replacement on any non- compatible equipment.

Mast Arms, Poles and Foundations

The existing 20' mast arm and pole, with anchor bolts, for the project shall be provided by the Town. The Contractor shall be responsible for the pick-up, transportation, and installation of the mast arm and pole.

The proposed 25' mast arm and pole shall be fabricated and constructed in conformance with the 2015 MassDOT Standard Drawings and as stated below.

The proposed 25' mast arm and pole shall be Type 2, galvanized steel monolever with shoe base. Acceptance of proposed Type 2 mast arm and pole will be contingent upon review and approval of shop drawings submitted by the Contractor. Longhand design calculations shall be submitted by the Contractor with the shop drawings for the proposed Type 2 mast arm pole.

The Contractor shall provide a set of calculations, stamped by a Structural Engineer registered in the Commonwealth of Massachusetts, along with plans and specifications for review by the Project Engineer for the proposed mast arm and pole.

The Contractor shall be responsible for performing all soil borings and soil classifications associated with the mast arms and poles. Reference is made to Items 191, 191.10, 191.11, and 193 for more information.

Prior to installation, the Contractor shall notify the Engineer in writing of his selection of mast arm foundation footing sizes.

All mast arm pole foundations shall be cored pier foundations and constructed in conformance with MassDOT Standard Drawings. Foundation sizes and depths shall be selected from the foundation design charts shown in MassDOT's Standard Drawings.

If ledge or unsuitable soil is encountered (i.e. on which does not apply to the design tables shown in MassDOT's standard drawings), an alternative design shall be provided by the Design Engineer. If utilities or other underground obstructions are encountered, the Contractor shall backfill the area to its original condition until an alternate design has been provided by the Design Engineer and approved by the Town.

No separate payment will be made for work considered incidental to the excavation, including but not limited to, mast arm foundations, dewatering, etc. but all costs in connection therewith shall be included in the contract lump sum bid price.

Foundations shall not obstruct a sidewalk or crosswalk so that passage by physically challenged persons is not impaired.

Signal Heads

Signal heads mounted on mast arms shall be rigidly attached to the mast arms. All signal heads mounted overhead on mast arms shall be installed, with the bottom of the signals at the same height. All traffic signal lenses shall be 12 inches in diameter. All signal heads shall be equipped with ball and/or arrow light emitting diode (LED) modules. Five (5) inch non-louvered backplates and tunnel visors shall be provided on all signal heads.

All backplates shall include 3-inch wide, yellow reflective micro-prismatic retroreflective sheeting conforming to ASTM D4956 Type VIII or better on the outside edge of the backplates.

Red, Yellow, and Green LED Vehicle Signal Module

All signal and pedestrian displays shall be equipped with LED signal modules. All red, amber, green, and pedestrian signal housings with the exception of optically programmed and fiber optic housings and shall conform to the following where applicable:

- ITE's Vehicle Traffic Control Signal Heads – Light Emitting Diode (LED) Arrow Traffic Signal Supplement, Dated July 1, 2007
- ITE's Vehicle Traffic Control Signal Heads – Light Emitting Diode (LED) Circular Signal Supplement, Dated June 27, 2005.
- ITE's Pedestrian and Countdown Signal Modules Compliant to PTCSI - Part 2 Light Emitting Diode (LED), Dated, February 2011
- On the MassDOT Traffic Signal Approved Equipment List

For an LED module to be installed on this project, the LED module shall have approval from the MassDOT Traffic Control Products Approved Equipment Committee and be included on the Traffic Control Products List prior to the date of this proposal.

To prevent the LED module warranty from being voided, the connecting leads on the module shall not be cut. The original LED module leads shall be connected to the signal head terminal block as continuous wire without splices.

The LED signal module will be replaced or repaired by the manufacturer if it exhibits one of the following:

- A failure due to workmanship or material defects within the first 60 months of field operation.
- A greater than 40 percent light output degradation or a fall below the minimum intensity levels (as defined by the latest ITE performance specifications) within the first 36 months of field operation.

Pedestrian Heads with Countdown Timers

All pedestrian heads shall be 16-inch, single units, with countdown timers. Pedestrian head indications shall be illuminated L.E.D. type displaying graphical symbols of a walking person and/or upraised hand. The countdown module shall display the number of seconds beginning at the start of the flashing “DON’T “WALK” interval, continue counting down through the flashing “DON’T WALK” interval, and blank out during the steady “DON’T WALK” interval. The countdown module shall be automatically set by the intersection controller based upon the “WALK” and “DON’T WALK” signal intervals only. The countdown module shall continuously monitor the intersection controller for any changes to the pedestrian phase timing, and reprogram itself automatically. All LED indications on the pedestrian signal shall have an automatic dimming circuit for night illumination to reduce long-term degradation to the LEDs.

Accessible Pedestrian Signal Pushbutton

The Accessible Pedestrian Signal (APS) pushbutton shall provide information in non-visual formats (such as audible tones, speech messages, and/or vibrating surfaces). The APS pushbuttons shall be compliant with the 2009 MUTCD. At a minimum the APS pushbuttons shall be provided with the following features:

- Pushbutton locator tone
- A visible and audible indicator that the button press has occurred
- A vibro-tactile arrow
- An audible walk message indication

The APS pushbuttons shall provide visually disabled pedestrians with a locator tone that will allow them to find the pushbutton to activate the walk signal. Once the pushbutton call has been placed, the signal will provide both an audible and tactile response during the related “WALK” portion of the cycle. A sunlight visible LED latches “ON” to confirm the button has been pushed.

Housing and Pushbutton Unit – Shall meet the following minimum requirements:

- Constructed of cast aluminum with a powder coated finish (black).
- Highly vandal resistant and pressure activated with essentially no moving parts.
- Operating temperature range -34 degrees Celsius to 65 degrees Celsius.
- Operating voltage range 12 to 36 VDC.
- Button cap must be made of solid 316 stainless steel.
- Pushbutton must activate with 5 lbs of force or less.
- Unit must have an LED display to give indication that of pushbutton being pushed.
- Pushbutton must fully operate immediately after being completely immersed in water for 5 minutes (electrical terminals isolated from water).

- Pushbutton must not allow ice to form such that it would impede function of pushbutton or pushbutton cap.
- All switch electronics must be sealed within the housing.
- All sounds shall emanate from the back of the of the APS pushbutton unit via a weatherproof speaker that is protected by a vandal resistant screen.

Tactile Arrows and Locator Tones – Shall meet the following minimum requirements:

- APS pushbuttons shall incorporate a locator tone at the pushbutton the locator tone, measured at 3 feet from the APS pushbutton, shall be 2dB minimum and 5dB maximum above ambient noise level in standard operation and shall be responsive to ambient noise level changes. Tones shall consist of multiple frequencies with a dominant component of 880Hz. The duration of the locator tone shall be 0.15s and shall repeat at intervals of 0.15s.
- APS pushbuttons shall be a minimum of 2 inches across in diameter and shall contract visually with their housing and mounting.
- APS pushbuttons shall include a vibro-tactile arrow aligned parallel to the crosswalk direction. The arrow shall be raised 0.03 inches minimum and shall be 1.5 inches minimum in length. The arrowhead shall be open at 45 degrees to the shaft and shall be 33 percent of the length of the shaft. Stroke width shall be 10 percent minimum and 15 percent maximum of arrow length. The arrow shall contrast with the background.
- The arrow shall vibrate during the “WALK” portion of the cycle.

Audible Walk Message – The audible walk message shall be audible from the beginning of the associated crosswalk. The audible walk message and associated APS pushbuttons shall be as follows:

PEDESTRIAN PUSHBUTTON	AUDIBLE WALK MESSAGE
P1-P4	Walk sign is on to cross street

Mounting Requirements - A maximum mounting height of 42 inches above the finish sidewalk grade shall be used for APS pedestrian pushbuttons.

The Contractor is hereby notified that they are ultimately responsible for constructing all pedestrian push button elements (clear ground space, forward and side arm reaches) in strict compliance with the current AAB rules, regulations and standards.

All construction elements in this project associated with pedestrian push buttons are controlled by 521CMR – Rules and Regulations of the Architectural Access Board. Pushbutton Frame Extenders shall be used if approved or directed by the Engineer.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

The Contractor shall establish clear ground space at all pedestrian push button locations and shall set arm reach lengths according to the AAB rules (or to the details shown on the plans).

The project has been designed to conform to all AAB rules, and the Engineer is not aware of any required variances for the work presented on the design plans. The Contractor shall notify the Engineer of any project element related to the pedestrian push buttons that will not comply with 521 CMR prior to constructing said pedestrian push button elements.

Installation - The APS pushbuttons shall be installed by Contractor and as recommended by the manufacturer and documented in installation materials provided by the manufacturer. The Contractor shall be responsible for the proper programming of the APS pushbuttons, orientation of the pushbuttons, and all other work necessary to provide a complete and operational APS pushbutton system. The Contractor may be required to adjust volume levels as directed by the Engineer. When the setup is complete and the APS pushbuttons are ready for operation, the values of all parameters that were set during the process shall be delivered to the Engineer in printed and computer-readable form.

Warranty - Each APS pushbutton shall be warranted free from defects in material and workmanship for a period of at least 2 years from the date of installation by the Contractor and acceptance from the owner.

During the warranty period, technical support shall be available from the supplier to the owner via telephone within 4 hours of the time a call is made by a user, and this support shall be available from factory-certified personnel without

Post and Base

Signal posts and bases shall be steel shafts with transformer bases.

Signal base foundations shall not obstruct a sidewalk or crosswalk so that passage by physically challenged persons is impaired.

Software

All local controller, malfunction management unit, and software shall be supplied with the latest available revision. Any software upgrades released by the manufacturer shall be supplied at no charge to the Owner for a period of five years after acceptance of the traffic signal installations.

Data Base Programming

Each programmable local hardware component (i.e., controller, malfunction management unit, video detection; and preemption unit) shall be initially programmed by the Contractor based on information contained on the plans.

Three sets of hard copy programming per device shall be supplied by the Contractor.

Equipment Finish and Color

Traffic signal equipment including but not limited to signal posts, bases, signal heads, visors, doors, mast arms, pushbutton saddles, controller cabinet (outside), service meter socket box, hardware, and rigid mounting brackets for signals and signs shall be colored **Semi-Gloss Black**, subject to the approval of the Town. The Contractor shall submit to the Engineer, and Town for approval, paint chips and sample finishes on aluminum and steel of the intended color prior to any work being done under this heading.

Signal heads, doors, visors, mounting brackets, and hardware supplied direct from the manufacturer in the color stipulated above may be acceptable provided it meets or exceeds the finish process for the material indicated below.

Steel Equipment

Galvanizing

All bolts, screws, nuts, rods and washers shall be galvanized in accordance with AASHTO M232 and the Standard Specifications. The hardened machine screws may be electroplate galvanized. Stainless steel studs, bolts, screws, nuts, straps and washers shall not be galvanized. Galvanized hardware need not be painted; however, the ends of bolts, nuts, and washers shall be painted in the field according to section "Touch-up and Repairs."

Immediately prior to galvanizing, the steel shall be immersed in a bath of zinc ammonium chloride. The dry kettle galvanizing process shall be used.

All steel components, other than above, shall be galvanized after fabrication in accordance with AASHTO M111. The galvanizing bath shall contain nickel (0.05% to 0.09% by weight) in accordance with subsection 960.61 of the Standard Specifications.

Galvanized members requiring shop assembly shall be welded and drilled prior to galvanizing.

Coating over Galvanized Steel

Prior to painting, the applicator shall ensure that all components are smooth and without sharp protrusions that would present and injury hazard to pedestrians. Also, the fabricator shall ensure that all welds shall be cleaned thoroughly in accordance with good practice and according to AWD D1.5 and ASTM A123-89a and shall have a suitable surface to accept the galvanizing.

In preparation for the two coat painting system, the surface shall be blast cleaned in accordance with the requirements of SSPC SP7 “Brush-Off Blast Cleaning” or other method producing equivalent results and uniform profile, to achieve a 1.0 to 1.5 mils anchor profile as indicated be a Keane Tator profile comparator or similar device. The creation of the anchor profile shall be performed prior to the formation of “white rust” on the galvanized surface.

Following blast cleaning, the zinc coating thickness shall be measured to verify that the coating thickness is in accordance with AASHTO M111.

A two-coat painting system shall be applied by the Galvanizer in his own facility within twelve hours of galvanizing the steel components.

The prime coat material shall be a polyamide epoxy applied to minimum dry film thickness of 2.0 to 4.0 mils (0.002-0.004 in.) and force cured as given below for the finish coat.

The finish coat material shall be a two component, catalyzed aliphatic urethane applied by airless spray to a minimum dry film thickness of 4.0 mils.

The color shall be per the **Semi-Gloss Black**. The fabricator shall submit to the Engineer for approval, paint chips of the intended color prior to any work being done under this heading.

All finish coat material shall be applied under conditions within the following tolerances:

1. Air Temperature: 50°F min., 90°F max.
2. Surface Temperature: 50°F min., 100°F max.
3. Surface temperature must be at least 5°F above the dew point.

The finish coat shall be cured in a booth capable of maintaining 150°F for 2-4 hours.

Touch-up and Repairs

Should any damage occur to the galvanized coating during shipping or handling at the job site, the Contractor shall repair and touch-up any damaged areas to the satisfaction of the Engineer and the following:

Touch-up of galvanizing before the finish coat is applied shall be accomplished by applying galvanizing repair paint in accordance with Section M7.04.11. The dry film thickness of the applied repair paint shall not be less than 4.0 mils.

Applications shall be in accordance with the manufacturer's instruction.

Field touch-up procedures shall conform to the recommendations of the galvanizer. Touch-up of the finish coat shall be by applying a coating of a two-part urethane, as supplied by the Galvanizer, to achieve a dry film thickness of at least 4.0 mils. Prior to the application of the paint, remove all damaged coatings down to a solidly adhered coating and apply galvanizing repair paint as primer.

Allow the primer to dry for at least 4 hours prior to top coating.

The Contractor shall also use the touch-up paint material and procedures to paint the galvanized hardware used in field erection that has not been finish coated previously.

Aluminum Equipment

All aluminum equipment called for shall have a powder coat finish. The coating shall be a polyester-TGIC (triglycidyl isocyanurat) resin system conforming to the following:

Quality	Test	Limits
Abrasion	Taber abraser CS-10, 1000 gram load, 1000 cycle, ASTM D4060	100 mg. Maximum weight loss
Adhesion	ASTM D .59 Initial 1000 hours	5A 5A
Gloss	ASTM D 523 60° - 600 hours 60° - 1000 hours	82% retention 90% retention (washed)
Hardness	ASTM D 3363	2H – No Gouge
Impact	ASTM D 2794 Direct	Pass 80 inch-lb.

Salt Spray Resistance	ASTM B 177 ASTM D 1654 1000 hours unscribed 400 hours scribed	Table 2-10 Table 1-10
Weather Resistant	ASTM G 23, 1000 hours, 18 min. waterspray, 102 min. light	No film failure
Color	<u>Semi-Gloss Black</u>	
Identify	Infrared fingerprint	Match
Flexibility	180° bend; $\frac{1}{2}$ " dia, mandrel within 10 seconds	No breaks, flaking or cracks. Tested with a Q-panel with 2 mils or less of coating
Humidity	ASTM D 2247, 1000 hours	No blister or film failure
Thickness		4 mils +/- 1 mils
Mar Resistance		Good

A Certificate of Compliance of the powder coating system is required for the Engineer's approval.

Wiring Diagram

Three sets of wiring diagrams with both internal and external wiring for the traffic signal control cabinet and all accessories as actually used in the field shall be furnished to the Town, including one mylar reproducible copy for the controller cabinet when installed. All actual and potential terminal strip connections shall be shown. Accessory equipment includes flashers, switches, relays, logic modules, preempt phase selectors, video detection, etc. All identification on the diagrams shall be as installed, and all field labeling shall be consistent with the diagram. Furthermore, the format symbols, identifications, operating sequence, etc., common to all the intersections wiring diagrams shall be standardized.

Manuals and Keys

The Contractor shall supply two (2) copies of operating and maintenance manuals (i.e., controller, malfunction management unit, preemption unit) and two (2) sets of cabinet keys to the Town.

Ownership and Maintenance

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

Upon acceptance of the traffic signal system by the Town, the Contractor shall turn over all guarantees and warranties to the Town, where applicable. In turn, the Town shall assume ownership and maintenance of the signal system.

ITEM 852.11 TEMPORARY PEDESTRIAN BARRICADE

ITEM 852.12 TEMPORARY PEDESTRIAN CURB RAMP

Work under these Items consist of furnishing, deploying, maintaining in proper operating conditions, and removing temporary pedestrian barricades and temporary pedestrian ramps as part of a Temporary Pedestrian Access Route (TPAR) in order to guide pedestrians around a fully- or partially-closed sidewalk. These devices are intended to prevent pedestrians from entering the work area and to prevent pedestrians from inadvertently entering the vehicle travel lane by providing visual and physical separation between each space.

MATERIALS

The Temporary Pedestrian Barricade shall have a continuous bottom rail or edge no more than two (2) inches above the ground and eight (8) inches in height (minimum) to accommodate cane users, have a smooth and continuous hand railing along the top edge no less than 32 inches above the ground and not obstruct or project into the pedestrian path of travel. Barricade walls shall be nearly vertical and generally within the same plane.

The Temporary Pedestrian Curb Ramp shall provide a 48-inch minimum width, with a firm, stable, and non-slip surface. Protective edging with a two (2) inch minimum height shall be installed when the curb ramp or landing platform has a vertical drop of six (6) inches or greater.

The Temporary Pedestrian Curb Ramp walkway and landing area surface shall be of a solid, continuous, contrasting color abutting up to the existing sidewalk.

If a Temporary Pedestrian Curb Ramp leads to a crosswalk, a detectable warning pad must be used at the base of the ramp; if it leads to a protected path that does not conflict with vehicular traffic then a detectable pad shall not be used.

CONSTRUCTION METHODS

The Temporary Pedestrian Barricade shall be placed in an area that will provide pedestrians with a TPAR on a smooth, continuous hard surface for its entirety. The geometry and alignment of the facility shall meet the applicable requirements of the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities" and the Massachusetts Architectural Access Board.

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

The recommended width of the TPAR is 60 inches, but if constraints exist a minimum clear width of 48 inches shall be provided along its entirety. If a 60 inch width cannot be accommodated in full, a 60 inch by 60 inch passing space shall be provided every 200 feet or less along the TPAR. Turning areas shall be 60 inches by 60 inches minimum.

Lateral joints between any surfaces shall not exceed 0.5 inches. Lateral edges may be vertical up to 0.25 inches high and shall be beveled at 1V:2H between 0.25 inches and 0.5 inches.

The TPAR shall be kept clear of debris, snow, and ice and the Temporary Pedestrian Barricades and Temporary Pedestrian Curb Ramps shall not obstruct drainage.

Removal and/or resetting of Temporary Pedestrian Barricades and Temporary Pedestrian Curb Ramps shall be considered incidental.

ITEM 860.104 4 INCH REFLECTORIZED WHITE LINE (PAINTED)

ITEM 860.112 12 INCH REFLECTORIZED WHITE LINE (PAINTED)

ITEM 861.104 4 INCH REFLECTORIZED YELLOW LINE (PAINTED)

Work under these items shall conform to the relevant provisions of Section 860 of the Standard Specifications and the following:

White and yellow pavement markings supplied under Items 860.104 and 861.104 shall conform to the applicable MassDOT's standards for 6 Inch Reflectorized White Line (Painted) and 6 Inch Reflectorized Yellow Line (Painted).

The work under these items shall consist of providing, installing, maintaining reflectorized white and yellow pavement marking lines, as shown on the plans or as directed by the Engineer.

ITEM 874.4 TRAFFIC SIGN REMOVED AND STACKED

The work under this item shall conform to the relevant provisions of Section 828 of the Standard Specifications and the following:

The work shall include the careful removal, transporting and stacking of traffic signs, attached hardware and supports from locations shown on the plans and as required by the Engineer, is salvageable.

Work shall also include excavation of existing foundations to a depth of at least 6 inches below grade, the supplying and placing of compacted gravel, and the restoration

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM

to original condition of any natural features disturbed in any way or manner by the operation.

The Contractor shall accept and hold entirely responsibility for the removal, handling and stacking at a location determined by the owner. Any signs and posts damaged or lost either directly or indirectly as a result of the Contractor's operations shall be replaced by the Contractor at no additional cost to the Owner.

The Contractor shall coordinate the removal of signs and posts with the City/Engineer prior to and at the completion of the above work. The Contractor shall coordinate with the Town to schedule drop-off time. Existing signs shall remain in place until proposed new signs are in place.

ITEM 999.1 POLICE SERVICES ALLOWANCE

The Contractor shall furnish police services required to direct traffic on existing roadways where traffic is maintained.

The Contractor shall provide such police officers as may be deemed necessary by either the Engineer or the Town for the direction and control of all traffic traveling within and through the project area. The police officers shall be obtained from the Town Police Department as applicable. The police officers shall be paid by the Contractor at the prevailing rate of wages established by the Town.

Allowance for Police Services

An allowance of Thirty Thousand Dollars (\$30,000.00) for the furnishing of police services has been included in all bids. This allowance is determined by multiplying the number of hours estimated as necessary by the prevailing hourly rate of wages established for such services. The Contractor shall submit certified copies of itemized bills of services rendered for review and approval by the Engineer. The allowance will be adjusted to the actual amount paid for authorized and approved police services as stipulated and shall include other payments due to any legal requirements of the State and Federal governments.

Payment

The quantity to be paid for under this item shall be the actual amount paid by the Contractor to provide satisfactory police services as stipulated and required. Any overhead costs shall be considered to be included in the contract lump sum price bid.

APPENDIX A – Prevailing Wage Rates

APPENDIX B – Plans

2025 Traffic Signal Improvement Project 25C-411-0044
Bid Opening March 5, 2025 at 10:00 AM